



NS0-515^{Q&As}

NetApp Certified Implementation Engineer - SAN, E-Series

Pass NetApp NS0-515 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/ns0-515.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Click the Exhibit button.

Referring to the exhibit, which three steps would you take to solve the problem shown in the event log? (Choose three.)

```
A:9/7/15 12:09:22 AM (07:09:22) 55985 1017 Fibre channel link down – Host-side: controller in slot A, port 2
A:9/7/15 12:09:22 AM (07:09:22) 55986 1018 Fibre channel link up – Host-side: controller in slot A, port 2
A:9/7/15 12:09:26 AM (07:09:26) 55990 1017 Fibre channel link down – Host-side: controller in slot A, port 2
A:9/7/15 12:09:26 AM (07:09:26) 55991 1018 Fibre channel link up – Host-side: controller in slot A, port 2
A:9/7/15 12:09:30 AM (07:09:30) 55993 1017 Fibre channel link down – Host-side: controller in slot A, port 2
A:9/7/15 12:09:30 AM (07:09:30) 55994 1018 Fibre channel link up – Host-side: controller in slot A, port 2
A:9/7/15 12:09:33 AM (07:09:33) 55996 1017 Fibre channel link down – Host-side: controller in slot A, port 2
A:9/7/15 12:09:33 AM (07:09:33) 55997 1018 Fibre channel link up – Host-side: controller in slot A, port 2
```

- A. Swap out the SFP in the controller port
- B. Swap out the FC cable
- C. Reinitialize the FC switch
- D. Move the connection to another controller port
- E. Swap out the HBA on the FC switch

Correct Answer: ABC

QUESTION 2

In which two locations would you find the WWPNs for a Windows host? (Choose two.)

- A. FC switch
- B. host\\\'s BIOS
- C. Windows Device Manager
- D. HBA vendor\\\'s utility

Correct Answer: AD

Reference: https://library.netapp.com/ecm/ecm_download_file/ECMP1532524 (7)

QUESTION 3

When a drive fails in a Dynamic Disk Pool (DDP) with no free capacity, what happens to the data?

- A. It is rebuilt using the on-board backup database



- B. It is rebuilt using preservation capacity within the DDP
- C. It is evacuated to the preservation capacity within the DDP
- D. It is evacuated to a hot spare drive that is assigned to the DDP

Correct Answer: B

Reference: <https://www.netapp.com/us/media/tr-4652.pdf> (6)

QUESTION 4

A company has a duplex E-Series system that is operating in a highly tuned environment. Load distribution between the controllers has been manually set up to achieve a specific distribution based on unique workload characteristics.

In this scenario, to maintain this load distribution over time, which E-Series feature should be disabled?

- A. Storage Load Balancer
- B. Automatic Node Balancer
- C. DNS Load Balancing
- D. Automatic Load Balancing

Correct Answer: D

Reference: <https://mysupport.netapp.com/NOW/public/eseries/sam/index.html#page/GUID-8538272AB802-49D9-9EA2-96C82DAD26A2/GUID-90A829B6-ACEE-41C6-8595-91C7D90554EB.html>

QUESTION 5

Click the Exhibit button.

Rock_Group

(Optimal) (14 drives, 17820.00 GiB capacity, [2 free capacity areas](#))



Secure-capable Yes (not enabled) | DA No

An administrator is asked to create a 5532 GiB volume from the volume group. Referring to the exhibit, how would the administrator complete this request?

- A. Create the volume after performing space reclamation
- B. Create the volume after consolidating the capacity
- C. Create the volume from the available capacity
- D. Create the volume after adjusting the preservation capacity



Correct Answer: C

[Latest NS0-515 Dumps](#)

[NS0-515 Study Guide](#)

[NS0-515 Exam Questions](#)