



# NSE7<sup>Q&As</sup>

Fortinet Troubleshooting Professional

## Pass Fortinet NSE7 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/nse7.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Which configuration can be used to reduce the number of BGP sessions in an IBGP network?

- A. Neighbor range
- B. Route reflector
- C. Next-hop-self
- D. Neighbor group

Correct Answer: B

---

**QUESTION 2**

View the following FortiGate configuration.

```
config system global
    set snat-route-change disable
end
config router static
    edit 1
        set gateway 10.200.1.254
        set priority 5
        set device "port1"
    next
    edit 2
        set gateway 10.200.2.254
        set priority 10
        set device "port2"
    next
end
```

All traffic to the Internet currently egresses from port1. The exhibit shows partial session information for Internet traffic from a user on the internal network:



```
# diagnose sys session list
session info: proto=6 proto_state=01 duration=17 expire=7 timeout=3600
flags=00000000 sockflag=00000000 sockport=0 av_idx=0 use=3
ha_id=0 policy_dir=0 tunnel=/
state=may_dirty none app_ntf
statistic(bytes/packets/allow_err): org=57555/7/1 reply=23367/19/1 tuples=2
origin->sink: org pre->post, reply pre->post dev=4->2/2->4
gwy=10.200.1.254/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:64907-
>54.239.158.170:80(10.200.1.1:64907)
hook=pre dir=reply act=dnat 54.239.158.170:80-
>10.200.1.1:64907(10.0.1.10:64907)
pos/(before, after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00000294 tos=ff/ff ips_view=0 app_list=0 app=0
dd_type=0 dd_mode=0
```

If the priority on route ID 1 were changed from 5 to 20, what would happen to traffic matching that user's session?

- A. The session would remain in the session table, and its traffic would still egress from port1.
- B. The session would remain in the session table, but its traffic would now egress from both port1 and port2.
- C. The session would remain in the session table, and its traffic would start to egress from port2.
- D. The session would be deleted, so the client would need to start a new session.

Correct Answer: D

### QUESTION 3

An administrator has configured a FortiGate device with two VDOMs: root and internal. The administrator has also created an inter-VDOM link that connects both VDOMs. The objective is to have each VDOM advertise some routes to the other VDOM via OSPF through the inter-VDOM link. What OSPF configuration settings must match in both VDOMs to have the OSPF adjacency successfully forming? (Choose three.)

- A. Router ID.
- B. OSPF interface area.
- C. OSPF interface cost.
- D. OSPF interface MTU.



E. Interface subnet mask.

Correct Answer: BDE

---

#### QUESTION 4

Examine the output of the `diagnose sys session list expectation` command shown in the exhibit; then answer the question below.

```
#diagnose sys session list expectation

session info: proto= proto_state=0 0 duration=3 expire=26 timeout=3600
flags=00000000
sockflag=00000000.sockport=0.av_idx=0.use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
ha_id=0.policy_dir=1.tunnel=
state=new complex
statistic (bytes/packets/allow_err): org=0/0/0 reply=0/0/0 tuples=2
origin-> sink: org pre-> post, reply pre->post dev=2->4/4->2
gwy=10.0.1.10/10.200.1.254
hook=pre dir=org act=dnat 10.171.121.38:0-> 10.200.1.1: 60426
(10.0.1.10: 50365)
hook= pre dir=org act=noop 0.0.0.0.:0-> 0.0.0.0:0 (0.0.0.0:0)
pos/(before, after) 0/(0,0), 0/(0,0)
misc=0.policy_id=1.auth_info=0.chk_client_info=0.vd=0
seriall=000000e9.tos=ff/ff.ips_view=0 app_list=0.app=0
dd type=0.dd_mode=0
```

Which statement is true regarding the session in the exhibit?

- A. It was created by the FortiGate kernel to allow push updates from FortiGuard.
- B. It is for management traffic terminating at the FortiGate.
- C. It is for traffic originated from the FortiGate.
- D. It was created by a session helper or ALG.

Correct Answer: A

---

#### QUESTION 5

View the exhibit, which contains a screenshot of some phase-1 settings, and then answer the question below.



Name	Remote
Comments	Comments

**Network**

IP Version	<input checked="" type="radio"/> IPv4 <input type="radio"/> IPv6
Remote Gateway	Static IP address
IP Address	10.0.10.1
Interface	port1
Mode Config	<input type="checkbox"/>
NAT Traversal	<input checked="" type="checkbox"/>
Keepalive Frequency	10
Dead Peer Detection	<input checked="" type="checkbox"/>

The VPN is up, and DPD packets are being exchanged between both IPsec gateways; however, traffic cannot pass through the tunnel. To diagnose, the administrator enters these CLI commands:

```
diagnose vpn ike log-filter src-add4 10.0.10.1
diagnose debug application ike-1
diagnose debug enable
```

However, the IKE real time debug does not show any output. Why?

- A. The debug output shows phases 1 and 2 negotiations only. Once the tunnel is up, it does not show any more output.
- B. The log-filter setting was set incorrectly. The VPN's traffic does not match this filter.
- C. The debug shows only error messages. If there is no output, then the tunnel is operating normally.
- D. The debug output shows phase 1 negotiation only. After that, the administrator must enable the following real time debug: `diagnose debug application ipsec -1`.

Correct Answer: D

[NSE7 VCE Dumps](#)

[NSE7 Practice Test](#)

[NSE7 Braindumps](#)