



NSE7_EFW-6.0^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 6.0

Pass Fortinet NSE7_EFW-6.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/nse7_efw-6-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

What is the purpose of an internal segmentation firewall (ISFW)?

- A. It is the first line of defense at the network perimeter.
- B. It inspects incoming traffic to protect services in the corporate DMZ.
- C. It is an all-in-one security appliance that is placed at remote sites to extend the enterprise network.
- D. It splits the network into multiple security segments to minimize the impact of breaches.

Correct Answer: D

QUESTION 2

View the exhibit, which contains the partial output of an IKE real-time debug, and then answer the question below.

```
ike 0:c49e59846861b0f6/0000000000000000:278: responder: main mode get 1st
message...
...
ike 0:c49e59846861b0f6/0000000000000000:278: incoming proposal:
ike 0:c49e59846861b0f6/0000000000000000:278: proposal id = 0:
ike 0:c49e59846861b0f6/0000000000000000:278:   protocol id = ISAKMP:
ike 0:c49e59846861b0f6/0000000000000000:278:   trans_id = KEY_IKE.
ike 0:c49e59846861b0f6/0000000000000000:278:   encapsulation = IKE/none
ike 0:c49e59846861b0f6/0000000000000000:278:   type=OAKLEY_ENCRYPT_ALG,
val=3DES_CBC.
ike 0:c49e59846861b0f6/0000000000000000:278:   type=OAKLEY_HASH_ALG,
val=SHA2_256.
ike 0:c49e59846861b0f6/0000000000000000:278:   type=AUTH_METHOD,
val=PRESHARED_KEY.
ike 0:c49e59846861b0f6/0000000000000000:278:   type=OAKLEY_GROUP,
val=MODP2048.
ike 0:c49e59846861b0f6/0000000000000000:278: ISAKMP SA lifetime=86400
...
ike 0:c49e59846861b0f6/0000000000000000:278: my proposal, gw VPN:
ike 0:c49e59846861b0f6/0000000000000000:278: proposal id = 1:
ike 0:c49e59846861b0f6/0000000000000000:278:   protocol id = ISAKMP:
ike 0:c49e59846861b0f6/0000000000000000:278:   trans_id = KEY_IKE.
ike 0:c49e59846861b0f6/0000000000000000:278:   encapsulation = IKE/none
ike 0:c49e59846861b0f6/0000000000000000:278:   type=OAKLEY_ENCRYPT_ALG,
val=AES_CBC, key-len=256
ike 0:c49e59846861b0f6/0000000000000000:278:   type=OAKLEY_HASH_ALG,
val=SHA2_256.
ike 0:c49e59846861b0f6/0000000000000000:278:   type=AUTH_METHOD,
val=PRESHARED_KEY.
ike 0:c49e59846861b0f6/0000000000000000:278:   type=OAKLEY_GROUP,
val=MODP2048.
ike 0:c49e59846861b0f6/0000000000000000:278: ISAKMP SA lifetime=86400
...
ike 0:c49e59846861b0f6/0000000000000000:278: negotiation failure
ike Negotiate ISAKMP SA Error: ike 0:c49e59846861b0f6/0000000000000000:278: no SA
proposal chosen
...
```



Why didn't the tunnel come up?

- A. The remote gateway is using aggressive mode and the local gateway is configured to use main mode.
- B. The remote gateway's phase 1 configuration does not match the local gateway's phase 1 configuration.
- C. The remote gateway's phase 2 configuration does not match the local gateway's phase 2 configuration
- D. The pre-shared keys do not match.

Correct Answer: B

QUESTION 3

What conditions are required for two FortiGate devices to form an OSPF adjacency? (Choose three.)

- A. OSPF IP MTUs match.
- B. OSPF costs match.
- C. OSPF peer IDs match.
- D. IP addresses are in the same subnet.
- E. Hello and dead intervals match.

Correct Answer: ADE

QUESTION 4

View the following FortiGate configuration.



```
config system global
    set snat-route-change disable
end
config router static
    edit 1
        set gateway 10.200.1.254
        set priority 5
        set device "port1"
    next
    edit2
        set gateway 10.200.2.254
        set priority 10
        set device "port2"
    next
end
```

All traffic to the Internet currently egresses from port1. The exhibit shows partial session information for Internet traffic from a user on the internal network.

```
FGT # diagnose sys session list
session info: proto=6 proto_state=01 duration=600 expire=3179 timeout=3600 flags=00000000
sockflag=00000000 sockport=0 av_idx=0 use=4
origin-shaper=
reply-shaper=
per_ip_shaper=
class_id=0 ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=log may_dirty npu f00
statistic(bytes/packets/allow_err): org=3208/25/1 reply=11144/29/1 tuples=2
tx speed(Bps/kbps): 0/0 rx speed(Bps/kbps): 0/0
origin->sink: org pre->post, reply pre->post dev=4->2/2->4 gwy=10.200.1.254/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:64907->54.239.158.170:80(10.200.1.1:64907)
hook=pre dir=reply act=dnat 54.239.158.170:80->10.200.1.1:64907(10.0.1.10:64907)
pos/(before,after) 0/(0,0), 0/(0,0)
src_mac=b4:f7:a1:e9:91:97
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00317c5b tos=ff/ff app_list=0 app=0 url_cat=0
rpd_b_link_id = 00000000
dd_type=0 dd_mode=0
npu_state=0x000c00
npu info: flag=0x00/0x00, offload=0/0, ips_offload=0/0, epid=0/0, ipid=0/0, vlan=0x0000/0x0000
vlifid=0/0, vtag_in=0x0000/0x0000 in_npu=0/0, out_npu=0/0, fwd_en=0/0, qid=0/0
no_ofld_reason:
```

If the priority on route ID 1 were changed from 5 to 20, what would happen to traffic matching that user's session?

- A. The session would be deleted, so the client would need to start a new session.
- B. The session would remain in the session table, and its traffic would still egress from port1.
- C. The session would remain in the session table, and its traffic would start to egress from port2.
- D. The session would remain in the session table, but its traffic would now egress from both port1 and port2.



Correct Answer: B

QUESTION 5

View the exhibit, which contains the output of diagnose sys session list, and then answer the question below.

```
# diagnose sys session list
session info: proto=6 proto_state=01 duration=73 expire=3597 timeout=3600
flags=00000000 sockflag=00000000 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
class_id=0 ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=may_dirty synced none app_ntf
statistic(bytes/packets/allow_err): org=822/11/1 reply=9037/15/1 tuples=2
origin->sink: org pre->post, reply pre->post dev=4->2/2->4
gwy=100.64.1.254/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:65464->54.192.15.182:80(100.64.1.1:65464)
hook=pre dir=reply act=dnat 54.192.15.182:80->100.64.1.1:65464(10.0.1.10:65464)
pos/(before,after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00000098 tos=ff/ff ips_view=0 app_list=0 app=0
dd_type=0 dd_mode=0
```

If the HA ID for the primary unit is zero (0), which one of the following statements about the output is true?

- A. This session is for HA heartbeat traffic.
- B. This session cannot be synced with the slave unit.
- C. The master unit is processing this traffic.
- D. The inspection of this session has been offloaded to the slave unit.

Correct Answer: C

[NSE7_EFW-6.0 Study Guide](#)

[NSE7_EFW-6.0 Exam Questions](#)

[NSE7_EFW-6.0 Braindumps](#)