



NSE7_EFW-6.4^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 6.4

Pass Fortinet NSE7_EFW-6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/nse7_efw-6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

When does a RADIUS server send an Access-Challenge packet?

- A. The server does not have the user credentials yet.
- B. The server requires more information from the user, such as the token code for two- factor authentication.
- C. The user credentials are wrong.
- D. The user account is not found in the server.

Correct Answer: B

QUESTION 2

What does the dirty flag mean in a FortiGate session?

- A. Traffic has been blocked by the antivirus inspection.
- B. The next packet must be re-evaluated against the firewall policies.
- C. The session must be removed from the former primary unit after an HA failover.
- D. Traffic has been identified as from an application that is not allowed.

Correct Answer: B

<https://kb.fortinet.com/kb/viewContent.do?externalId=FD40119andslicId=1>

QUESTION 3

Examine the output of the ``diagnose sys session list expectation\`\`` command shown in the exhibit; than answer the question below.



```
#diagnose sys session list expectation

session info: proto= proto_state=0 0 duration=3 expire=26 timeout=3600
flags=00000000
sockflag=00000000.sockport=0.av_idx=0.use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
ha_id=0.policy_dir=1.tunnel=/
state=new complex
statistic (bytes/packets/allow_err): org=0/0/0 reply=0/0/0 tuples=2
origin-> sink: org pre-> post, reply pre->post dev=2->4/4->2
gwy=10.0.1.10/10.200.1.254
hook=pre dir=org act=dnat 10.171.121.38:0-> 10.200.1.1: 60426
(10.0.1.10: 50365)
hook= pre dir=org act=noop 0.0.0.0.:0-> 0.0.0.0:0 (0.0.0.0:0)
pos/(before, after) 0/(0,0), 0/(0,0)
misc=0.policy_id=1.auth_info=0.chk_client_info=0.vd=0
serial=000000e9.tos=ff/ff.ips_view=0 app_list=0.app=0
dd type=0.dd_mode=0
```

Which statement is true regarding the session in the exhibit?

- A. It was created by the FortiGate kernel to allow push updates from FortiGuard.
- B. It is for management traffic terminating at the FortiGate.
- C. It is for traffic originated from the FortiGate.
- D. It was created by a session helper or ALG.

Correct Answer: D

QUESTION 4

Refer to the exhibit, which contains the debug output of diagnose dvm device list.

```
FMG-VM64# diagnose dvm device list
There are currently 1 devices/vdoms managed:
TYPE      OID      SN      HA      IP      NAME      ADOM      IPS      FIRMWARE
fmg/      217     FGVM01... -      10.200.1.1 Local-FortiGate My_ADOM 15.0.0831 6.0 MR4 (1579)
faz enabled
          |- STATUS: db: modified; conf: in sync; cond: pending; dm: retrieved; conn: up
          |- vdom: [3] root flags:0 adom:My_ADOM pkg: [imported] Local-FortiGate_root
```

Which two statements about the output shown in the exhibit are correct? (Choose two.)



- A. ADOMs are disabled on the FortiManager
- B. The FortiGate configuration is in sync with latest running revision history.
- C. There are pending device-level changes yet to be installed on Local-FortiGate.
- D. The policy package has been modified for Local-FortiGate.

Correct Answer: BC

Reference: <https://docs.fortinet.com/document/fortimanager/7.0.0/upgrade-guide/959309/cli-example-ofdiagnose-dvm-device-list>

QUESTION 5

Refer to the exhibit, which contains partial outputs from two routing debug commands.

```
FortiGate # get router info routing-table database
S      0.0.0.0/0 [20/0] via 100.64.2.254, port2, [10/0]
S      *> 0.0.0.0/0 [10/0] via 100.64.1.254, port1

FortiGate # get router info routing-table all
S*     0.0.0.0/0 [10/0] via 100.64.1.254, port1
```

Why is the port2 default route not in the second command's output?

- A. It has a higher priority value than the default route using port1.
- B. It is disabled in the FortiGate configuration.
- C. It has a lower priority value than the default route using port1.
- D. It has a higher distance than the default route using port1.

Correct Answer: D

[NSE7_EFW-6.4 VCE Dumps](#)

[NSE7_EFW-6.4 Practice Test](#)

[NSE7_EFW-6.4 Exam Questions](#)