



NSE7_OTS-6.4^{Q&As}

Fortinet NSE 7 - OT Security 6.4

Pass Fortinet NSE7_OTS-6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/nse7_ots-6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

An OT supervisor needs to protect their network by implementing security with an industrial signature database on the FortiGate device.

Which statement about the industrial signature database on FortiGate is true?

- A. A supervisor must purchase an industrial signature database and import it to the FortiGate.
- B. An administrator must create their own database using custom signatures.
- C. By default, the industrial database is enabled.
- D. A supervisor can enable it through the FortiGate CLI.

Correct Answer: D

QUESTION 2

An OT network administrator is trying to implement active authentication.

Which two methods should the administrator use to achieve this? (Choose two.)

- A. Two-factor authentication on FortiAuthenticator
- B. Role-based authentication on FortiNAC
- C. FSSO authentication on FortiGate
- D. Local authentication on FortiGate

Correct Answer: AB

QUESTION 3

Refer to the exhibit.



Based on the Purdue model, which three measures can be implemented in the control area zone using the Fortinet Security Fabric? (Choose three.)

- A. FortiGate for SD-WAN
- B. FortiGate for application control and IPS
- C. FortiNAC for network access control
- D. FortiSIEM for security incident and event management
- E. FortiEDR for endpoint detection

Correct Answer: BCD

QUESTION 4

Refer to the exhibit.

Router/Switch Image Distribution						
Active Rules x Windows Installed Patches x Router/Switch Image Distribution x						
Back Export						
1/1						
Device Name	Device Type Vendor	Device Type Model	Device Hardware Model	Device Image File	Count	
SJ-QA-A-IOS-JunOffice	Cisco	IOS	1760	C1700-advsecurityk9-mz 123-8.T4.bin	1	
SJ-Main-Cat6500	Cisco	IOS	WS-C6509	s72033-advipservicesk9_wan-mz 122-33.SX11.bin	1	
ph-network-3560_1	Cisco	IOS	WS-C3560G-48PS-S	c3560-advipservicesk9-mz 122-25.SEE4.bin	1	

An OT administrator ran a report to identify device inventory in an OT network. Based on the report results, which report was run?



- A. A FortiSIEM CMDB report
- B. A FortiAnalyzer device report
- C. A FortiSIEM incident report
- D. A FortiSIEM analytics report

Correct Answer: A

QUESTION 5

An OT network architect must deploy a solution to protect fuel pumps in an industrial remote network. All the fuel pumps must be closely monitored from the corporate network for any temperature fluctuations.

How can the OT network architect achieve this goal?

- A. Configure a fuel server on the remote network, and deploy a FortiSIEM with a single pattern temperature security rule on the corporate network.
- B. Configure a fuel server on the corporate network, and deploy a FortiSIEM with a single pattern temperature performance rule on the remote network.
- C. Configure a fuel server on the remote network, and deploy a FortiSIEM with a single pattern temperature performance rule on the corporate network.
- D. Configure both fuel server and FortiSIEM with a single-pattern temperature performance rule on the corporate network.

Correct Answer: B

[NSE7_OTS-6.4 PDF Dumps](#)

[NSE7_OTS-6.4 VCE
Dumps](#)

[NSE7_OTS-6.4 Braindumps](#)