



# NSE7\_SDW-7.0<sup>Q&As</sup>

Fortinet NSE 7 - SD-WAN 7.0

## Pass Fortinet NSE7\_SDW-7.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

[https://www.pass4itsure.com/nse7\\_sdwan-7-0.html](https://www.pass4itsure.com/nse7_sdwan-7-0.html)

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Refer to exhibits. Exhibit A.

Link Status

Check interval	500	ms
Failures before inactive	3	
Restore link after	2	check(s)

Actions when Inactive

Update static route ☒

Exhibit B.

```
NGFW-1 # diagnose sys sdwan health-check
Health Check (Ping):
Seq (1 port1): state (alive), packet-loss (0.000%) latency
(6.196), jitter (0.079) sla_map=0x0
Seq (2 port2): state (dead), packet-loss (6.000%) sla_map=0x0
```

Exhibit A, which shows the SD-WAN performance SLA and exhibit B shows the health of the participating SD-WAN members. Based on the exhibits, which statement is correct?

- A. The dead member interface stays unavailable until an administrator manually brings the interface back.
- B. The SLA state of port2 has exceeded three consecutive unanswered requests from the SLA server.
- C. Static routes using port2 are active in the routing table.
- D. FortiGate has not received three consecutive requests from the SLA server configured for port2.

Correct Answer: D

**QUESTION 2**








Refer to exhibits.



## Exhibit A

## Exhibit B

## Edit Policy

Name 	Internet Access		
Incoming interface	 port3	▼	
Outgoing interface	 virtual-wan link	▼	
Source	 all	+	x
Destination	 all	+	x
Schedule	 always	▼	
Service	 ALL	+	x
Action	<input checked="" type="checkbox"/> ACCEPT <input type="checkbox"/> DENY		
Inspection Mode	<input checked="" type="checkbox"/> Flow-based <input type="checkbox"/> Proxy-based		

## Firewall / Network Options

NAT	<input checked="" type="checkbox"/>
IP Pool Configuration	<input checked="" type="checkbox"/> Use Outgoing Interface Address <input type="checkbox"/> Use Dynamic
Preserve Source Port	<input type="checkbox"/>
Protocol Options	<input checked="" type="checkbox"/> PROT default ▼



Exhibit A

Exhibit B

Edit Traffic Shaping Policy

Name

inbound\_outbound\_shaper

Status

Enabled

Disabled

Comments

Write a comment...

0/255

If Traffic Matches:

Source

all

+

x

Destination

all

+

x

Schedule

☐

Service

ALL

+

x

Application

+

URL Category

Streaming Media and Download

+

x

Then:

Action

Apply Shaper

Assign Shaping Class ID

Outgoing interface

virtual-wan link

+

x

Shared shaper

☒

guarantee-10mbps

▼

Exhibit A shows the firewall policy and exhibit B shows the traffic shaping policy.

The traffic shaping policy is being applied to all outbound traffic; however, inbound traffic is not being evaluated by the shaping policy.

Based on the exhibits, what configuration change must be made in which policy so that traffic shaping can be applied to inbound traffic?



- A. Create a new firewall policy, and the select the SD-WAN zone as Incoming Interface.
- B. In the traffic shaping policy, select Assign Shaping Class ID as Action.
- C. In the firewall policy, select Proxy-based as Inspection Mode.
- D. In the traffic shaping policy, enable Reverse shaper, and then select the traffic shaper to use.

Correct Answer: D

### QUESTION 3

Refer to the exhibit.

```
branch1_fgt # diagnose sys sdwan service 1

Service(3): Address Mode(IPV4) flags=0x200 use-shortcut-sla
Gen(6), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(manual)
Members(2):
  1: Seq_num(3 T_INET_0_0), alive, selected
  2: Seq_num(4 T_INET_1_0), alive, selected
Src address(1):
  10.0.1.0-10.0.1.255

Dst address(1):
  10.0.0.0-10.255.255.255

branch1_fgt # diagnose sys sdwan member | grep T_INET_
Member(3): interface: T_INET_0_0, flags=0x4 , gateway: 100.64.1.1, priority: 10 1024,
weight: 0
Member(4): interface: T_INET_1_0, flags=0x4 , gateway: 100.64.1.9, priority: 0 1024,
weight: 0

branch1_fgt # get router info routing-table all | grep T_INET_
S      10.0.0.0/8 [1/0] via T_INET_1_0 tunnel 100.64.1.9
```

An administrator is troubleshooting SD-WAN on FortiGate. A device behind branch1\_fgt generates traffic to the 10.0.0.0/8 network. The administrator expects the traffic to match SD-WAN rule ID 1 and be routed over T\_INET\_0\_0. However, the traffic is routed over T\_INET\_1\_0.

Based on the output shown in the exhibit, which two reasons can cause the observed behavior? (Choose two.)

- A. The traffic matches a regular policy route configured with T\_INET\_1\_0 as the outgoing device.
- B. T\_INET\_1\_0 has a lower route priority value (higher priority) than T\_INET\_0\_0.
- C. T\_INET\_0\_0 does not have a valid route to the destination.
- D. T\_INET\_1\_0 has a higher member configuration priority than T\_INET\_0\_0.

Correct Answer: AC



#### QUESTION 4

Which diagnostic command can you use to show the SD-WAN rules interface information and state?

- A. diagnose sys sdwan route-tag-list.
- B. diagnose sys sdwan service.
- C. diagnose sys sdwan member.
- D. diagnose sys sdwan neighbor.

Correct Answer: B

<https://community.fortinet.com/t5/FortiGate/Technical-Tip-Diagnostic-commands-to-check-the-status-of-the-SD/tap/194246>

---

#### QUESTION 5

Which are three key routing principles in SD-WAN? (Choose three.)

- A. FortiGate performs route lookups for new sessions only.
- B. Regular policy routes have precedence over SD-WAN rules.
- C. SD-WAN rules have precedence over ISDB routes.
- D. By default, SD-WAN members are skipped if they do not have a valid route to the destination.
- E. By default, SD-WAN rules are skipped if the best route to the destination is not an SD- WAN member.

Correct Answer: BDE

[Latest NSE7 SDW-7.0 Dumps](#)

[NSE7 SDW-7.0 Exam Questions](#)

[NSE7 SDW-7.0 Braindumps](#)