



PW0-105^{Q&As}

Certified Wireless Network Administrator (CWNA)

Pass CWNP PW0-105 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/pw0-105.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Given:

A WLAN transmitter that emits a 200 mW signal is connected to a cable with 3 dB loss.

If the cable is connected to an antenna with 10 dBi gain, what is the EIRP at the antenna element?

- A. 10 dBm
- B. 13 dBm
- C. 20 dBm
- D. 26 dBm
- E. 30 dBm

Correct Answer: E

QUESTION 2

What features are most often configurable within 802.11 WLAN client utilities? (Choose two)

- A. Frame generator utility
- B. Power management
- C. Co-channel interference threshold
- D. Roaming aggressiveness
- E. AES key and block size

Correct Answer: BD

QUESTION 3

What statement about 802.3af Power over Ethernet (802.3, Clause 33) is true?

- A. If a dual-radio access point requires 12W to operate, a PoE power source supplies 15.4W to the powered interface.
- B. 802.3af-compliant endpoint and midspan PSE devices support 10/100 as well as Gigabit (1000BaseT) data rates.
- C. Class 1 powered devices may use a maximum of 29W of power.
- D. 802.3af-compliant Ethernet switches must be able to simultaneously support class 3 powered devices on every powered interface.
- E. There are two classes of 802.3af PSEs: Type A supports up to 7W and Type B supports up to 15W of supplied power.



Correct Answer: A

QUESTION 4

In an 802.11n WLAN with a heterogeneous set of associated client devices including 802.11b, 11g, and 11n, what HT protection mode will the BSS use?

- A. Mode 0: No protection mode (Greenfield)
- B. Mode 1: Nonmember protection mode
- C. Mode 2: 20 MHz protection mode
- D. Mode 3: Non-HT mixed mode

Correct Answer: D

QUESTION 5

What facts are true regarding controllers and APs in a Split MAC architecture? (Choose 2)

- A. An IP tunnel is established between the AP and controller for AP management and control functions.
- B. Using centralized data forwarding, APs never tag Ethernet frames with VLAN identifiers or 802.1p CoS.
- C. With 802.1X/EAP security, the AP acts as the supplicant and the controller acts as the authenticator.
- D. Management and data frame types must be processed locally by the AP, while control frame types must be sent to the controller.
- E. In a distributed (local bridging) data forwarding model, the AP handles frame encryption and decryption.

Correct Answer: AE

[PW0-105 PDF Dumps](#)

[PW0-105 VCE Dumps](#)

[PW0-105 Study Guide](#)