RHCE Q&As

Red Hat Certified Engineer — RHCE

Pass RedHat RHCE Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/rhce.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by RedHat Official Exam Center

- **Instant Download** After Purchase
- **100% Money Back** Guarantee
- **365 Days** Free Update
- **800,000+** Satisfied Customers

QUESTION 1

SIMULATION

There were two systems: system1, main system on which most of the configuration take place system2, some configuration here Configure repository. Create a Repository for your virtual machines. The URL is http://station.network.0.example.com/content/rhel7.0/x86_64/dvd

A. explanation

Correct Answer: A

```
# vim /etc/yum.repos.d/local.repo

[localrepo]
name = Local Repo for RHCE Exam
baseurl = http://station.network0.example.com/content/rhel7.0/x86_64/dvd
gpgcheck = 0
enabled = 1
```

Save and Exit (:wq) Then run this:

```
# yum clean all
# yum repolist
```

QUESTION 2

SIMULATION

Whoever creates the file on /data make automatically owner group should be the group owner of /data directory.

A. explanation

Correct Answer: A

When user creates the file/directory, user owner will be user itself and group owner will be the primary group of the user. There is one Special Permission SGID, when you set the SGID bit on directory. When users create the file/directory automatically owner group will be same as a parent.

1.

chmod g+s /data

2.

Verify using: ls -ld /data You will get: drwxrws--

QUESTION 3

SIMULATION

Shutdown the /root/cdrom.iso under /opt/data and set as boot automatically mount.

A. explanation

Correct Answer: A

```
# cd /opt/
# mkdir data
# mount -t iso9660 -o loop /root/cdrom.iso /opt/data
# vim /etc/fstab
   /root/cdrom.iso /opt/data iso9660 defaults,loop 0 0
# mount -a
# mount
```

QUESTION 4

SIMULATION

There were two systems: system1, main system on which most of the configuration take place system2, some configuration here

Configure SCSI storage. Create a new 1 GB target on your serverX.example.com The block device name should be data_block The server should export an iscsi disk called iqn.2014-10.com.example:serverX This target should only be allowed to desktop

A. explanation

Correct Answer: A

```
yum install -y targetcli
systemctl start target
systemctl enable target
firewall-cmd --permanent --add-port=3260/tcp
firewall-cmd -reload

#targetcli
backstores/block/create data-block /dev/sdb1
iscsi/ create iqn.2014-10.com.example:server1
cd iscsi/iqn.2014-10.com.example:server1/tpg1/
acls create iqn.2014-10.com.example:desktop1
luns/ create backstores/block/data_block
portals Server_IP(172.25.x.11) 3260
exit
```

QUESTION 5

SIMULATION

According to the following requirements, deploy your ftp login rule:

Users in example.com domain must be able to login to your ftp server as an anonymous user.

But users outside the example.com domain are unable to login to your server

A. explanation

Correct Answer: A

```
[root@server1 ~]# grep vsftpd /etc/hosts.deny
vsftpd: .example.com

[root@server1 ~]# grep vsftpd /etc/hosts.deny
vsftpd:ALL

/etc/vsftpd/vsftpd.conf:
anonymous_enable=YES
```

RHCE VCE Dumps RHCE Study Guide RHCE Braindumps