



VCS-273^{Q&As}

Administration of Veritas NetBackup 7.6.1 and NetBackup Appliances
2.6.1

Pass Veritas VCS-273 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/vcs-273.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Veritas
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A policy is created using the Standard policy type. The default settings are used. Linux hosts s1 and s2 are added in the client list and ALL_LOCAL_DRIVES is specified in the Backup Selection. Host s1 has the mount points listed below: / /opt /usr /usr/home Host s2 has the mount points listed below: / /proc /tmp /usr How many streams will be created when the policy runs for both clients?

- A. two
- B. four
- C. five
- D. eight

Correct Answer: A

QUESTION 2

Which NetBackup utility should an administrator use to determine I/O performance of the appliance storage and network?

- A. nbperfchk
- B. nbdna
- C. datacollect
- D. nbsu

Correct Answer: A

QUESTION 3

An administrator has backups failing with status code 96 due to tapes being prevented from returning to the scratch volume pool after the images they contain expire. What prevented the media from returning to the scratch pool?

- A. media was created in volume pools other than the scratch pool
- B. media was in an off-site location
- C. media was written with multiplexed images
- D. an application other than NetBackup wrote to the media

Correct Answer: A



QUESTION 4

An administrator discovers that backup images configured with a fixed two-week retention are failing to expire.

What is a possible cause of this issue?

- A. the disk pool containing the images is unavailable
- B. secondary SLP operations on the images are incomplete
- C. the tape containing the images is frozen
- D. the disk storage unit is capacity-managed

Correct Answer: B

QUESTION 5

An administrator is running an appliance upgrade from 2.6.0.1 to 2.6.1 and the appliance Web UI is inaccessible throughout the upgrade process. How should the administrator check the progress of the upgrade using the CLISH?

- A. Manage > Software > UpgradeStatus
- B. Manage > Software > UpgradeState
- C. Manage > Software > UpgradeProgress
- D. Manage > Software > UpgradeCheck

Correct Answer: A

[VCS-273 PDF Dumps](#)

[VCS-273 Practice Test](#)

[VCS-273 Braindumps](#)