

Exam : 000-M43

Title : IBM SUT Intermediate Level
Technical Sales Mastery
Test V1.0

Version : Demo

www.Pass4itSure.com

1. The following is true of a business group (BG)?
- A. Each BG has at least one common numbering plan (CNP).
 - B. Each BG has at least one private numbering plan (PNP).
 - C. There is no geographical boundary for a BG.
 - D. A and B
 - E. B and C

Answer: E

2. Why is it advisable to have at least one PNP for SUT subscribers and a separate PNP and endpoint for the customer's PBX?

- A. It allows Display Number Modification (DNM) rules to be created separately for subscribers' calls to the PBX, and incoming calls from the PBX.
- B. It allows digits to be added/deleted for the call coming from the PBX.
- C. SUT subscribers need extra attention during configuration.
- D. A and B

Answer: D

3. Which of the following is correct regarding SUT configurations?

- A. There is no conference server available in the small SUT configuration, only in the large SUT configuration.
- B. Besides the Sametime Server, a small SUT configuration needs one single server while a large SUT configuration needs three servers.
- C. One media server is required per location.
- D. The small SUT configuration uses one server for TAS and Media Server.
- E. A and D

Answer: D

4. Assume there is a company using SUT with 1 Headquarter and 2 locations each in Europe, America and Asia. In each site there are 100 subscribers and there is one PBX and one PSTN Gateway. In the Headquarter, there is a Media Server for Announcements and Conferencing. Each subscriber has a SUT Client and a Desk phone. Which of the answers below would match to a best practice numbering plan configuration?

- A. One common numbering plan and ten private numbering plans.
- B. One common numbering plan and nine private numbering plans.
- C. One common numbering plan and six private numbering plans.
- D. One common numbering plan and three private numbering plans.
- E. Three common numbering plans and three private numbering plans.

Answer: B

5. What are mandatory parameters that need to be adjusted at both end points of a SIP trunk?

- A. The MTU size.
- B. The preferred codec.
- C. The Music On Hold number.
- D. The target IP address and the port number.

Answer: D

www.Pass4itSure.com

Trying our product !

- ★ **100%** Guaranteed Success
- ★ **100%** Money Back Guarantee
- ★ **365 Days** Free Update
- ★ **Instant Download** After Purchase
- ★ **24x7** Customer Support
- ★ Average **99.9%** Success Rate
- ★ More than **69,000** Satisfied Customers Worldwide
- ★ Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



Submit A Ticket

One Year Free Update



Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.



Money Back Guarantee

To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.



Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.

Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.