

100% Money Back Guarantee

Vendor: Citrix

Exam Code: 1Y0-253

Exam Name: Implementing Citrix NetScaler 10.5 for App and Desktop Solutions

Version: Demo

QUESTION 1

A Citrix Administrator needs to configure a single virtual server to accept TCP traffic on ports 80, 443 and ports between 10000 and 19999.

Which protocol type should the administrator use to accomplish this task?

- A. ANY
- B. UDP
- C. SSL_TCP
- D. SSL_PUSH

Correct Answer: A

QUESTION 2

Which two pieces of information are required to create a virtual server? (Choose two.)

- A. Port
- B. Protocol
- C. Subnet Mask
- D. Gateway Address

Correct Answer: AB

QUESTION 3

Which two items are needed to import an SSL certificate? (Choose two.)

- A. A public key
- B. A private key
- C. A root certificate
- D. A server certificate
- E. An intermediate certificate

Correct Answer: BD

QUESTION 4

Scenario: A company requires two-factor authentication using RSA tokens and Active Directory. The Citrix Administrator configured the following two authentication policies with these parameters:

- The policy named RSA_policy is used for RSA token authentication
- The policy named AD_policy is used for Active Directory authentication

What should the administrator do to protect the NetScaler Gateway virtual server from an attack against Active Directory?

- A. Bind the RSA_policy in Primary Authentication Policies and bind the AD_policy in Secondary Authentication Policies.
- B. Bind the AD_policy in Primary Authentication Policies and bind the RSA_policy in Secondary Authentication Policies.
- C. Bind the AD_policy and the RSA_policy in Primary Authentication Policies and set the RSA_policy priority higher than the AD_policy.
- D. Bind the AD_policy and the RSA_policy in Primary Authentication Policies and set the AD_policy priority higher than the RSA_policy.

Correct Answer: A

QUESTION 5

Various users report that while accessing the Citrix NetScaler Gateway virtual server they get an error message that the public SSL certificate is NOT trusted.

Which three steps should a Citrix Administrator take on the NetScaler to resolve this issue? (Choose three.)

- A. Import the root certificate.
- B. Import the intermediate certificate.
- C. Download the root certificate from the vendor.
- D. Link the root certificate to the intermediate certificate.
- E. Download the intermediate certificate from the vendor.
- F. Link the intermediate certificate to the existing server certificate.

Correct Answer: BEF

QUESTION 6

A Citrix Administrator needs to configure NetScaler Gateway to communicate with the StoreFront providing resources hosted on XenApp and XenDesktop.

Which IP address does the NetScaler use to route user connections to the StoreFront?

- A. Subnet IP (SNIP)
- B. NetScaler IP (NSIP)
- C. User Source IP (USIP)
- D. Client IP (CIP)

Correct Answer: A

QUESTION 7

Scenario: A Citrix Administrator is implementing a NetScaler appliance for the first time. All clients will connect from a public network and all servers will reside on a private network.

Which deployment mode should the administrator use to implement the NetScaler?

- A. Layer 2 (L2) mode
- B. Layer 3 (L3) mode
- C. Two-arm deployment mode
- D. MAC-based forwarding mode

Correct Answer: C

QUESTION 8

Which two IP addresses are required for a new NetScaler Gateway installation when using the First-Time Setup Wizard? (Choose two.)

- A. Client IP (CIP)
- B. Virtual IP (VIP)
- C. Subnet IP (SNIP)
- D. NetScaler IP (NSIP)

Correct Answer: AB

QUESTION 9

Which IP address must be unique on each node in a high availability configuration?

- A. Virtual IP (VIP)
- B. Mapped IP (MIP)
- C. Subnet IP (SNIP)
- D. NetScaler IP (NSIP)

Correct Answer: B

QUESTION 10

Which component is required to allow users to launch Worx Home through a NetScaler Gateway?

- A. App Controller
- B. Citrix Receiver
- C. Citrix StoreFront
- D. NetScaler Gateway Plug-in

Correct Answer: C

QUESTION 11

Scenario: A company is considering using NetScaler appliances to load balance existing secured web servers. The company compliance policy does NOT allow any alterations of the SSL sessions between clients and web servers.

Which option should a Citrix Administrator configure on the NetScaler virtual server to meet the needs of the company?

- A. SSL VPN
- B. SSL Bridge
- C. SSL Offload
- D. SSL Renegotiation

Correct Answer: B

QUESTION 12

Which two steps must a Citrix Administrator take to allow additional users to access resources using the NetScaler Gateway Plug-in after the administrator installs the universal license on the NetScaler Gateway? (Choose two.)

- A. Set ICA Proxy to OFF.
- B. Configure Citrix Receiver Home Page.
- C. Change the authentication AAA settings.
- D. Set Single Sign-on with Windows to OFF.

Correct Answer: AC

QUESTION 13

Which two parameters are required for adding a new node to a cluster? (Choose two.)

- A. Cluster IP of the new cluster node
- B. NetScaler IP of the new cluster node
- C. NetScaler IP of the existing cluster node
- D. Remote NetScaler user name and password
- E. Backplane interface of the existing cluster node

Correct Answer: BD

QUESTION 14

Scenario: Users report that they are being presented with a certificate error when they attempt to access the remote access website of the company. No changes were made to the NetScaler certificates recently.

What should the Citrix Administrator check on the NetScaler to identify this issue?

- A. Cert Links
- B. OCSP Binding

- C. Certificate Format
- D. Certificate Expiry Date

Correct Answer: D

QUESTION 15

Which monitor should a Citrix Administrator configure to monitor a StoreFront server group with SSL enabled?

- A. TCP
- B. SSL_TCP
- C. STOREFRONT with "Secure" checked
- D. CITRIX-WEB-INTERFACE with "Secure" checked

Correct Answer: D

QUESTION 16

What should be done to ensure high availability (HA) failover in a NetScaler HA configuration?

- A. Disable all unused system interfaces.
- B. Disable the IPv6 feature on the NetScaler.
- C. Enable all used and unused system interfaces.
- D. Change the NetScaler HA setup to two-arm mode.

Correct Answer: A

QUESTION 17

A Citrix Administrator needs to track load balanced traffic from the NetScaler to separate, individual subnets.

Which IP address should be used to do this?

- A. Virtual IP (VIP)
- B. Mapped IP (MIP)
- C. NetScaler IP (NSIP)
- D. Subnet IP (SNIP)

Correct Answer: D

QUESTION 18

Scenario: A Citrix Administrator is configuring user authentication on the NetScaler Gateway. The administrator wants to use the same login name that is used to log into Windows-based domain joined workstations.

Which Server Logon Name Attribute should be used?

- A. memberOf
- B. displayName
- C. sAMAccountName
- D. userAccountControl

Correct Answer: C

QUESTION 19

Two StoreFront servers in an environment need to be addressed with a single URL.

Which feature should a Citrix Administrator enable to meet this requirement?

- A. SSL VPN

- B. Load Balancing
- C. Integrated Caching
- D. Application Firewall

Correct Answer: A

QUESTION 20

Which two steps must a Citrix Administrator complete to configure the SSL Offloading feature on a NetScaler appliance? (Choose two.)

- A. Create a DNS virtual server.
- B. Configure an AAA virtual server.
- C. Create an SSL VPN virtual server.
- D. Create a load balancing virtual server.
- E. Import a valid certification-key pair and bind it to the virtual server.

Correct Answer: DE

QUESTION 21

A Citrix Administrator needs to mask the server name used by a web server, without exposing the web server virtual directory structure.

Which policy should the administrator use to complete this task?

- A. Responder
- B. Content Filtering
- C. Content Switching
- D. URL Transformation

Correct Answer: D

QUESTION 22

A Citrix Administrator is replacing an expired SSL certificate bound to a virtual server.

The established ICA connections to the virtual server will display as _____. (Choose the correct option to complete the sentence.)

- A. logged off
- B. terminated
- C. disconnected
- D. uninterrupted

Correct Answer: C

QUESTION 23

At the onset of a XenDesktop 7.5 with NetScaler Gateway 10.5 proof-of-concept, users report they are unable to access desktop and server OS machines.

Which configuration might be preventing users from accessing desktop and server OS machines?

- A. Single-hop DMZ with StoreFront
- B. Double-hop DMZ with StoreFront
- C. Single-hop DMZ with Web Interface
- D. Double-hop DMZ with Web Interface

Correct Answer: B

QUESTION 24

Which two NetScaler components are needed to deploy a NetScaler Gateway solution for an existing

To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Trying our product !

- ★ **100%** Guaranteed Success
- ★ **100%** Money Back Guarantee
- ★ **365 Days** Free Update
- ★ **Instant Download** After Purchase
- ★ **24x7** Customer Support
- ★ Average **99.9%** Success Rate
- ★ More than **69,000** Satisfied Customers Worldwide
- ★ Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.	 Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.	 Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.
---	---	--

Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.