



1Y0-230^{Q&As}

Citrix NetScaler 12 Essentials and Unified Gateway

Pass Citrix 1Y0-230 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1y0-230.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which mode on the NetScaler can a Citrix Administrator utilize to avoid asymmetrical packet flows and multiple route/ARP lookups?

- A. USNIP
- B. Layer 3
- C. MAC-based Forwarding
- D. Layer 2

Correct Answer: C

Explanation: MAC-based forwarding can be used to avoid multiple-route/ARP lookups and to avoid asymmetrical packet flows. Reference: [https://docs.citrix.com/en-us/netscaler/11/networking/interfaces/configuring-mac-based](https://docs.citrix.com/en-us/netscaler/11/networking/interfaces/configuring-mac-based-forwarding.html)

[forwarding.html](https://docs.citrix.com/en-us/netscaler/11/networking/interfaces/configuring-mac-based-forwarding.html)

QUESTION 2

Which two options should a Citrix Administrator configure to stop the First-Time wizard from automatically popping up? (Choose two.)

- A. Host Name is NOT configured on the appliance
- B. The appliance is configured with the default IP address (192.168.100.1)
- C. the default Admin Password has NOT been changed
- D. Licenses are NOT present on the appliance

Correct Answer: BD

Reference: <https://docs.citrix.com/ja-jp/netscaler/11/netscaler-hardware-installation/netscaler-initialconfiguration.html>

QUESTION 3

A Citrix Administrator is configuring a Citrix ADC high availability (HA) pair and needs to ensure that one Citrix ADC is UP and primary at all times to ensure the business websites are always available.

What does the administrator need to do ensure that the Citrix ADCs still handle web traffic in the event that both nodes become unavailable or fail a health check?

- A. Disable HA Fail-safe mode on the Secondary Citrix ADC.
- B. Configure HA Fail-safe mode on each Citrix ADC independently.
- C. Disable HA Fail-safe mode on the Primary Citrix ADC only.



D. Configure HA Fail-safe mode on the Primary Citrix ADC only.

Correct Answer: D

Reference: <http://www.citrixguru.com/2015/09/14/lab-part-6-configure-netscaler-11-high-availability-hapair/>

QUESTION 4

Which two actions must be true for a client to connect to a SSL offload virtual server without any SSL errors? (Choose two.)

- A. The Root Certificate is installed on the client's device
- B. The Server Certificate is bound to the load-balancing virtual server
- C. The Server Certificate is from a private certificate authority (CA)
- D. The Root Certificate is installed on the NetScaler

Correct Answer: AC

QUESTION 5

Scenario: A Citrix Administrator has given permissions to team members to access their own admin partition, so they can add resources for different departments and manage them without making changes to the default NetScaler partition and configuration.

One team member was trying to use the command-line interface to trouble an authentication issue and could NOT use `aaad.debug`. However, the team member has full permissions on the admin partition.

What can be the cause of this issue?

- A. The team member needs to troubleshoot the issue from the GUI.
- B. The team member does NOT have Shell access by design.
- C. The team member does NOT have permission to use the CLI.
- D. The team member is NOT using the CLI correctly.

Correct Answer: C

QUESTION 6

Scenario: A Citrix Administrator is concerned about the amount of health checks the NetScaler is sending the back-end resources. The administrator would like to find a way to remove health checks from specific bound services.

How can the administrator accomplish this?

- A. Use reverse condition monitoring.



- B. Use Service Groups to minimize health checks.
- C. Unbind the current monitor.
- D. Use the No-Monitor Option.

Correct Answer: C

QUESTION 7

Which three NetScaler features can a Citrix Administrator use for default syntax policies? (Choose three.)

- A. SSL
- B. Rewrite
- C. Integrated caching
- D. Protection
- E. Responder

Correct Answer: ABE

Reference <https://docs.citrix.com/zh-cn/netscaler/11/appexpert/policies-and-expressions/ns-pi-intro-polexp-wrapper-con/ns-pi-adv-class-pol-con.html>

QUESTION 8

Scenario: A Citrix Administrator of a Linux environment needs to load-balance the web servers in an environment. However, due to budget constraints, the administrator is NOT able to implement a full-scale solution.

What can the administrator do to load-balance the web servers in this scenario?

- A. Install a NetScaler CPX.
- B. Purchase NetScaler MPX.
- C. Purchase a NetScaler SDX.
- D. Install NetScaler VPX.

Correct Answer: A

QUESTION 9

Scenario: A Citrix Administrator suspects an attack on a load-balancing virtual server. The administrator needs to restrict access to the load-balancing virtual server (192.168.100.25) for 10 minutes.

Which Access Control List (ACL) will help to accomplish this requirement?



- A. add ns acl rule1 DENY –destIP 192.168.100.25- TTL 600000
- B. add simpleacl rule1 DENY- srcIP 192.168.100.25- TTL 600
- C. add ns acl rule1 DENY –destIP 192.168.100.25- TTL 600
- D. add simpleacl rule1 DENY- srcIP 192.168.100.25- TTL 600000

Correct Answer: C

Reference: <https://docs.citrix.com/ja-jp/netscaler/11/reference/netscaler-command-reference/ns/nsacl.html>

QUESTION 10

Scenario: A Citrix Administrator notices user sessions are disconnecting and reconnecting more often this week than last week, signaling a problem.

The administrator troubleshoots this issue and prepares to resolve it using persistence. However, the following considerations apply in the environment:

- It is a multi-proxy environment behind the NetScaler.
- USIP mode is enabled and applied to the services.
- The session timeout is very short.
- All users connect from the same location.

The Administrator can use persistence based on the _____ setting to resolve this issue. (Choose the correct option to complete the sentence.)

- A. HTTP Cookies
- B. Proximity
- C. SSL Session IDs
- D. Subnet IP

Correct Answer: A

QUESTION 11

Which two deployment methods does remote desktop protocol (RDP) proxy support? (Choose two.)

- A. ICA proxy
- B. Two hops
- C. Optimal Gateway
- D. CVPN



Correct Answer: AD

Reference: <https://docs.citrix.com/en-us/netscaler-gateway/12/rdp-proxy.html>

QUESTION 12

A Citrix Administrator needs to generate AppFlow data for internal ICA connections.

Which two connection methods could the administrator use to route internal ICA connections through NetScaler without modifying the existing network routing? (Choose two.)

- A. Policy-based Routing
- B. ICA Proxy
- C. SOCKS proxy
- D. Transparent Mode

Correct Answer: AD

QUESTION 13

Scenario: A Citrix Administrator has made changes to the Citrix ADC, deleting parts of the configuration, and then saved the new configurations. The changes caused an outage which needs to be resolved as quickly as possible. There is no Citrix ADC backup.

What does the administrator need to do to recover the configuration quickly?

- A. Restart the Citrix ADC
- B. Run Save v/s Running configuration
- C. Restore from revision history
- D. Run HA file synchronization

Correct Answer: D

QUESTION 14

A Citrix Administrator receives user complaints about latency while accessing an application that is being load-balanced on the NetScaler.

Which tool can the administrator use to gather information regarding Response time, Client latency and Server-side processing time?

- A. aaad.debug



B. WAN Insight

C. NetScaler Management and Analytics System (MAS)

D. HDX Insight

Correct Answer: D

Reference: https://www.citrix.com/content/dam/citrix/en_us/documents/products-solutions/solve-theapplication-visibility-challenge-with-netscaler-insight-center.pdf

QUESTION 15

Scenario: User authentication is failing through the NetScaler. A Citrix Administrator checked the Authentication, Authorization and Auditing (AAA) policy, action and virtual server and verified that the correct configuration was in place. The administrator bypassed the NetScaler and the authentication worked. Which NetScaler utility can the administrator use to troubleshoot the access issue?

A. nslog file

B. aaad.debug

C. nscon message

D. Dashboard

Correct Answer: B

[1Y0-230 PDF Dumps](#)

[1Y0-230 Study Guide](#)

[1Y0-230 Braindumps](#)