



1Y0-253^{Q&As}

Implementing Citrix NetScaler 10.5 for App and Desktop Solutions

Pass Citrix 1Y0-253 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1y0-253.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

An administrator plans to use only Citrix Receiver for XenDesktop remote access through a NetScaler Gateway device.

Which type of policy should the administrator configure to meet this requirement?

- A. Session
- B. Authentication
- C. Clientless access
- D. Pre-authentication

Correct Answer: A

QUESTION 2

An administrator is reviewing the following output:

```
vIP(141.128.58.149:80:UP:WEIGHTEDRR): Hits(38200495, 18jsec) Mbps(1.02) Pers(OFF) Err(0) Pkt (186jsec, 610 bytes) actSvc(4) DefPol(NONE) override(0)
```

```
Conn: Clt(253, 1jsec, OE[252/]) Svr(3) S(141.128.49.40:80:UP) Hits(9443063, 4jsec, P[2602342, 0jsec])
```

```
ATr(5) Mbps(0.23)BWlmt(100 kbits) RspTime(112.58 ms)
```

```
Other: Pkt(36jsec, 712 bytes) Wt(10000) RHits(31555)
```

```
Conn: CSvr(42, 0jsec)MCSvr(20)OE(16)RP(11)SQ(0)
```

How much traffic is being passed through the public IP address based on the output displayed above?

- A. 100 kbits
- B. 1.02 Mbps
- C. 0.23 Mbps
- D. 112.58 ms

Correct Answer: B

QUESTION 3

Scenario: A Citrix Administrator is implementing a NetScaler appliance for the first time. All clients will connect from a public network and all servers will reside on a private network.



Which deployment mode should the administrator use to implement the NetScaler?

- A. Layer 2 (L2) mode
- B. Layer 3 (L3) mode
- C. Two-arm deployment mode
- D. MAC-based forwarding mode

Correct Answer: C

QUESTION 4

A Citrix Administrator needs to ensure that published applications are available to users through StoreFront.

Which monitor type should the administrator use to ensure that services are available?

- A. HTTP
- B. HTTP-ECv
- C. STOREFRONT
- D. CITRIX-WEB-INTERFACE

Correct Answer: C

QUESTION 5

Which IP address does NetScaler use for Active Directory authentication?

- A. virtual IP (vIP)
- B. Client IP (CIP)
- C. NetScaler IP (NSIP)
- D. Subnet IP (SNIP)

Correct Answer: D

QUESTION 6

Which NetScaler IP address type is created when the below command is executed at the command-line interface?

```
add ns ip 192.168.2.1 255.255.255.0
```

- A. virtual IP



- B. Cluster IP
- C. Subnet IP
- D. Mapped IP
- E. GSLB Site IP

Correct Answer: C

QUESTION 7

Scenario: A Citrix Administrator would like to delegate administration of the Citrix NetScaler to a Microsoft Active Directory group called ICitrix-NetScaler-Adminsl. The group already exists in Active Directory. The Citrix- NetScaler-Admins group must have full-control permission on the Citrix NetScaler to perform their tasks. The administrator has successfully configured an LDAP authentication server and authentication policy. The authentication policy is already globally bound. How should the administrator proceed on the Citrix NetScaler?

- A. Create an AAA User called Citrix-NetScaler-Admins and select IExternal Authenticationl.
- B. Create a group called Citrix-NetScaler-Admins. Make the group a member of the operator command policy.
- C. Create a group called Citrix-NetScaler-Admins. Make the group a member of the superuser command policy.
- D. Create an AAA group called Citrix-NetScaler-Admins. Create an ALLOW authorization policy and bind it to the Citrix-NetScaler-Admins AAA Group.

Correct Answer: C

QUESTION 8

Scenario: A Citrix Administrator is upgrading a high availability pair to NetScaler 10.5. After upgrading the secondary appliance, the administrator forces a failover to test the new firmware, but the show ha node command shows the sync state and propagation as disabled.

Why are the settings showing as disabled?

- A. The appliances did NOT properly failover.
- B. The NSIPs are no longer able to communicate.
- C. The settings are automatically disabled until the other appliance is upgraded.
- D. The upgrade process failed to run to completion on the secondary appliance.

Correct Answer: C

QUESTION 9

Scenario: A Citrix Administrator created a new NetScaler Gateway virtual server. During testing, users are



unable to access XenApp applications through iOS and Android devices.

Which configuration should the administrator verify?

- A. Clientless Access is set to OFF.
- B. Client Cleanup prompt is selected.
- C. The virtual server is set to Basic Mode.
- D. Single Sign-on to Web Applications is selected.

Correct Answer: A

QUESTION 10

Which two methods should be used for generating a configuration data and statistics report for evaluation by Citrix? (Choose two.)

- A. Run Ishow callhome1 using the command-line interface.
- B. Run Ishow techsupport1 using the command-line interface.
- C. Click the Call Home link under the Technical Support Tools section in the NetScaler Configuration Utility.
- D. Click the Download trace files link under the Technical Support Tools section in the NetScaler Configuration Utility.
- E. Click the Generate support file link under the Technical Support Tools section in the NetScaler Configuration Utility.

Correct Answer: BE

QUESTION 11

Scenario: A virtual server has been configured in the Content Switching node to provide multiple Web services using the full website path location. This website contains details that can only be displayed using a specific Web browser such as Internet Explorer. Which two actions must an administrator perform to ensure that users are informed of the browser requirements? (Choose two.)

- A. Configure Advanced Expression policies to determine the type of browser used.
- B. Create a backup server to display a website that informs users of the browser requirements.
- C. Configure a redirect URL to redirect users to a website that informs them of the browser requirements.
- D. Configure a default policy to redirect users to a website that informs them of the browser requirements.

Correct Answer: AD

QUESTION 12

Scenario: A Citrix Administrator has configured Outlook Web Access by means of a Citrix NetScaler AAA



virtual server.

Users complain that they need to re-authenticate after 30 minutes of inactivity. Users work all day from

Outlook Web Access.

Which configuration change should an administrator make to ensure the session is available the entire workday?

- A. Session time-out in 480 (minutes).
- B. Enable Persistent Cookie validity in 480 (minutes).
- C. Set Client Idle Time-out to 10800 (seconds) on the Outlook Web Access virtual server.
- D. Set Client Idle Time-out to 10800 (seconds) on the Outlook Web Access Service (group).

Correct Answer: B

QUESTION 13

Scenario: A backend web server is NOT functioning correctly due to a database related issue. The web server is load balanced by Citrix NetScaler. Due to the database issue, the correct content is NOT being displayed. However the NetScaler is still allowing connections to the web server. How can a Citrix Administrator prevent this from happening?

- A. Create an SQL database user within NetScaler.
- B. Create two monitors, one on the webserver that checks on HTTP and one on the database server that checks on TCP.
- C. Create an HTTP monitor on the webserver that checks on a pattern that originates from the database within the HTML code.
- D. Create an HTTP-ECv monitor on the webserver that checks on a pattern that originates from the database within the HTML code.

Correct Answer: D

QUESTION 14

Which two tasks must a Citrix Administrator complete to enable Client Certificate Authentication on the NetScaler Gateway? (Choose two.)

- A. Create a pre-authentication policy.
- B. Create an LDAP authentication policy.
- C. Import the root certificate onto the NetScaler Gateway.
- D. Import all client certificates onto the NetScaler Gateway.
- E. Enable the Client Authentication option on the virtual server.



Correct Answer: CE

QUESTION 15

An administrator is planning a NetScaler Gateway implementation and must ensure that users are only allowed to access the company resources if a specific file is present on the endpoint device they connect from.

Which component should the administrator include within the plan?

- A. An SSL Offload virtual server
- B. A double-hop NetScaler Gateway virtual server
- C. A Basic mode NetScaler Gateway virtual server
- D. A SmartAccess mode NetScaler Gateway virtual server

Correct Answer: D

[1Y0-253 PDF Dumps](#)

[1Y0-253 Practice Test](#)

[1Y0-253 Braindumps](#)