



1Z0-432^{Q&As}

Oracle Real Application Clusters 12c Essentials

Pass Oracle 1Z0-432 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1z0-432.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



**QUESTION 1**

If you upgrade to ASM 12cR1 and implement Flex ASM, do you need to upgrade all the databases to 12cR1?

- A. Yes. All the databases need to be upgraded to 12cR1
- B. No. You can run in a mixed 11.2 database instance and a 12cR1 database instance. The 11.2 instance will use the Flex ASM instance of the other server.
- C. No. You can run in a mixed 11.2 database instance and a 12cR1 database instance, but the 11.2 instance will fail if the local Flex ASM instance is moved to another server
- D. No. You cannot upgrade your database instance to 12cR1

Correct Answer: C

QUESTION 2

On a new Oracle Grid Infrastructure 12cR1 system, you notice that Oracle Flex ASM has been configured. Which two reasons are valid for configuring Grid Infrastructure in this manner?

- A. Increased high availability of database instances
- B. Simple grid infrastructure configuration and easier maintenance
- C. Increased spare memory on reserved nodes
- D. Better performance for the underlying storage hardware

Correct Answer: AB

QUESTION 3

A node in a four-node cluster encounters corruption on the OLR and must be restored from backups taken using clusterware utilities. Identify the option that shows the correct OLR restore commands.

- A. `crsctl stop crsocrconfig -local -restore /my_olr_backup_locationocrcheck -local crsctl start crs cluvfy comp olr`
- B. `ocrdump -local -backupfile /my_olr_backupocrcheck -local`
- C. `crsctl stop crsocrdump -restore -backupfile +DG_FRA/myolr_backupocrcheck -local crsctl start crs`
- D. `crsctl stop crsocrconfig -local -manualbackupocrconfig -local -restore /my_olr_backup_locationcluvfy comp olrcrsctl start crs`
- E. `crsctl stop crsocrcheck -local -restore /my_olr_backup_locationcluvfy comp olrcrsctl start crs`

Correct Answer: A

**QUESTION 4**

Which two components are included in Oracle CloudFS?

- A. ASM Cluster File System
- B. Oracle Database
- C. Oracle ASM Dynamic Volume Manager
- D. Oracle Clusterware

Correct Answer: AC

QUESTION 5

Identify the correct srvctl command to add the crm01 instance to the COB RAC 12cR1 database crm on the gm01 node.

- A. Srvctl add cdb instance -db crm -instance crm01 -node gm01
- B. Srvctl add instance -db crm -instance crm01 -node gm01
- C. Srvctl add non-cdb instance -db crm -instance crm01 -node gm01
- D. Srvctl add pdb instance -db crm -instance crm01 -node gm01

Correct Answer: B

QUESTION 6

Oracle 12cR1 Flex Cluster introduces a new topology, which allows for a higher level of scalability. Which four statements accurately describe the new topology's properties?

- A. Hub and Leaf topologies allow tightly and loosely coupled server membership
- B. Hub and Leaf topologies support implicit Server Pools.
- C. Leaf servers are standard as in previous versions.
- D. Leaf servers are light-weight, no shared storage, no peer-to-peer communication and dedicated to application service.
- E. Hub servers do not support Oracle ASM.
- F. Oracle Flex Cluster 12cR1 supports bare metal and OVM servers in common cluster

Correct Answer: ABDF

QUESTION 7



Which statement about Allocation Units is incorrect?

- A. Every Oracle ASM disk is divided into allocation units (AUs)
- B. An AU is the fundamental unit of allocation within a disk group
- C. A file extent consists of one or more AUs
- D. The au size disk group attribute can have the following values; 1, 8, 16, 32, 64, or 128 MB.

Correct Answer: D

QUESTION 8

A node is evicted from a three-node cluster due to poor latency of the underlying storage Which two statements are correct in describing the instance recovery process?

- A. Perform a restore of archive redo from flash recovery area to recover database
- B. Upon startup, the SMON/LMS processes perform instance crash recovery.
- C. Upon startup of failed instance, the SMON process performs instance crash recovery by using checkpoints to determine which data needs to be append to data files.
- D. User intervention is not required.
- E. Upon startup, PMON (process monitor) performs instance crash recovery automatically User intervention is not required

Correct Answer: CD

QUESTION 9

You want to start the ASM1 instance on node host01. Which three options can you use?

- A. `$ srvctl start asm -n host01`
- B. `$ srvctl status asm -n host01`
- C. `$ asmca Disk Groups - > Mount All`
- D. `$. oraenv`

ORACLE_SID = (+ASM1) ? +ASM1The Oracle base for ORACLE_HOME=/u01/app/12.1.0/grid is /u01/app/grid

S asmcmd

ASMCMD (+) > shutdown -abort

- E. `$. oraenv`

ORACLE_SID = (+ASM1) ? +ASM1The Oracle base for ORACLE_HOME=/u01/app/12.1.0/grid is /u01/app/grid



S asmcmd

ASMCMD> startup

F. \$ export ORACLE_SID =+ASM1\$ export ORACLE_HOME=/u01/app/12.1.0/grid

\$ \$ORACLE_HOME/bin/squiplus/AS SYSASM

SQL> startup

Correct Answer: AEF

QUESTION 10

You are building a new 12c cluster to accommodate the upcoming projects. You are currently working with the network admin team to define the requirements needed. Currently, the network team would like to get cleared on the protocols being used by the various network interface needed. Which three statements about Clusterware communication are correct?

- A. For the public network, each network adapter must support TCP/IP. This requirement holds true for both Microsoft Windows and Linux/Unix environments
- B. For the private network, the interface must support the user datagram protocol (UDP) using high speed network adapters and switches that support TCP/IP. This holds true in the Linux/Unix environment.
- C. For the public network, each network adapter needs to support only UDP, which provides low latency. This requirement holds true for both Microsoft Windows and Linux/Unix environments
- D. For the private network, the network adapters must use high-speed network adapters and switches that support TCP/IP. This requirement holds true in the Microsoft Windows environment
- E. There is no mandatory requirement for the protocol being supported for both private and public interfaces. Oracle RAC and Clusterware automatically detect and support any current standard industry protocol

Correct Answer: ABD

QUESTION 11

The DISK_REPAIR_TIME attribute has expired after a transient disk error. What happens next?

- A. Nothing, it was only a warning. All the disks are OK
- B. This means that the disk is repaired and is put back in the ASM disk group.
- C. Oracle ASM drops the disk.
- D. This means that Oracle will use ASM Fast Mirror Resync to sync the rest of the disks.

Correct Answer: C

QUESTION 12



Which statement about the `srvctl modify instance` command is correct?

- A. For a policy-managed database, this command defines an instance name to use when the database runs on the specified node.
- B. For an administrator-managed database, this command restores the configuration of a database instance
- C. You can use this command to rename or relocate a running instance.
- D. This command is only available with Oracle RAC One Node.

Correct Answer: A

QUESTION 13

Which three statements accurately describe the components of the Cluster Ready Services Technology Stack?

- A. Cluster Ready Services (CRS): A specialized oraagent process that helps CRSD manage resources owned by root such as the network, and the Grid virtual IP address
- B. Cluster Synchronization Services (CSS): Manages the cluster configuration by controlling which nodes are members of the cluster and by notifying members when a node joins or leaves the cluster
- C. Cluster Time Synchronization Service (CTSS): A background process that publishes events that Oracle Clusterware creates.
- D. Event Management (EVM). Provides time management in a cluster for Oracle Clusterware
- E. Grid Naming Service (GNS): Handles requests sent by external DNS servers, performing name resolution for names defined by the cluster.
- F. Oracle Agent (oraagent): This process was known as RACG in Oracle Clusterware 11gR1 (11.1).

Correct Answer: BEF

QUESTION 14

You are preparing two Oracle Linux nodes, node1 and node2, for the installation of Oracle Grid Infrastructure, you plan to use the existing Linux users "grid" as Grid Infrastructure software. What task must be performed before installing the Grid Infrastructure?

- A. Change the user "grid" initial login group to "dba"
- B. No task must be performed.
- C. Change the user ID of the grid user in node1, node2, or both nodes to guarantee that the user IDs are equal
- D. Add "users" to supplementary groups of "grid" in node1. Or, alternatively remove "users" from supplementary groups of node2 "grid."
- E. Use another Linux user as "grid" might be used for other purposes.

Correct Answer: C



QUESTION 15

Under which condition can Oracle Automated Storage Management (ASM) be considered to be a component of the Oracle Clusterware technology stack?

- A. Oracle Cluster Registry (OCR) is stored on Oracle ASM
- B. Oracle Local Registry (OLR) is stored on a clustered file system (OCFS/ACFS/DBFS)
- C. Both Oracle Cluster Registry and Oracle Local Registry are stored on Oracle ASM
- D. Oracle ASM can never be considered a component of Oracle Clusterware
- E. Oracle ASM can be considered a component of Oracle Clusterware technology stack only when deployed on engineered systems such as Exadata or Oracle Database Appliance

Correct Answer: A

[1Z0-432 VCE Dumps](#)

[1Z0-432 Study Guide](#)

[1Z0-432 Braindumps](#)