



210-065^{Q&As}

Implementing Cisco Video Network Devices

Pass Cisco 210-065 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/210-065.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

Refer to the exhibit.



For Cisco TelePresence endpoints with TC7.0 software, configuration backup and restore appears where?

- A. Call Control tab
- B. Configuration tab
- C. Diagnostics tab
- D. Maintenance tab
- E. Home tab

Correct Answer: D



Reference: <http://www.cisco.com/c/dam/en/us/td/docs/telepresence/endpoint/quick-set-sx20/tc7/administration-guide/sx20-quickset-administrator-guide-tc70.pdf>

QUESTION 2



Management wants to modify Cisco TMS to allow users to configure the call behavior with their associated devices and dial from a single ID. Which feature needs to be enabled and configured?

- A. Smart Scheduler
- B. Low-touch Provisioning
- C. FindMe
- D. CMR Provisioning

Correct Answer: C

With FindMe, you can be reached on any device using a single ID. You can define your locations and specify which endpoints are available to you in those locations. You can also specify which endpoints (video and audio only) should ring when someone calls your FindMe ID. FindMe also allows you to specify additional devices to be called if the default devices are busy or not answered. Administrators can configure account IDs for each user, set up location and device templates, and choose whether to add new devices to FindMe automatically on provisioning. You can create FindMe accounts to define forwarding rules for groups such as support desks. The FindMe portal is located on the Cisco TMS Server, where you can log on with your Active Directory credentials. You can access your Cisco TMSPE account settings, see your username and video address (Session Initiation Protocol Uniform Resource Locator [SIP URI]), and change your provisioning password.

Reference: http://www.cisco.com/c/en/us/products/collateral/conferencing/telepresence-management-suite-tms/data_sheet_c78-707901.html

QUESTION 3

Refer to the exhibit.

**Search (453)****State:** Completed**Found:** False**Reason:** Forbidden**Info:** Policy Response**Type:** SIP (INVITE)**Call Serial Number:** 948f15f9-10e9-45f6-9ce5-8c825de615fc**Tag:** ebbb35fc-9175-4b32-a37b-ca4e08e6478d**Source (1)****Authenticated:** True**Aliases (1)****Alias (1)****Type:** Url**Origin:** Unknown**Value:** 15551001234@domain.com**Zone (1)****Name:** CUCM**Type:** Neighbor**Path (1)****Hop (1)****Address:** 10.10.10.10:5060**Destination (1)****Alias (1)****Type:** Url**Origin:** Unknown**Value:** sip: 15558005678@10.20.30.40:5060**StartTime:** 2014-09-30 15:08:10**Duration:** 0**Sub Search (1)****Type:** Transforms**Action:** Transformed**ResultAlias (1)****Type:** H323id**Origin:** Unknown**Value:** 15558005678@domain.com**Sub search (1)****Type:** Admin Policy**Action:** Reject

A technician is reviewing the search history details on a Cisco TelePresence VCS for a recent call that failed. What was the cause for the call setup failure?

- A. A local call policy rule denied the call.
- B. The source alias matched an entry in the registration deny list.
- C. The originating caller was not authenticated.



D. The source alias origin is unknown.

Correct Answer: A

QUESTION 4

Endpoints for immersive telepresence (Choose three): A. CTS 3000

B. TX 9000

C. EX 90

D. SX 10

E. T3

F. Jabber

Correct Answer: ABE

QUESTION 5

Which two features are provided by Cisco TelePresence Management Suite? (Choose two.)

A. Scheduling of video conference calls

B. Built-in-bridge functionality for multiparty video conferences

C. Cisco TelePresence endpoint automated redundancy

D. SIP-H.323 protocol interworking

E. endpoint configuration backup and restore

Correct Answer: AE

QUESTION 6

Refer to the exhibit. You must dial the interactive response system of the multipoint control unit. What are the appropriate dual-tone multi-frequency digits to create an ad-hoc conference with an identifier of 2345?



Cisco TelePresence Video Communication Server Control

Status System VCS configuration Applications Maintenance**Registrations by device**

Name ▾	E.164	Type	Protocol
<input type="checkbox"/> 5002@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5911@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5912@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5913@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5914@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5915@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5916@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5919@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5921@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5922@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5923@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5924@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5925@osl147.local		SIP UA	SIP
<input type="checkbox"/> 5926@osl147.local		SIP UA	SIP
<input type="checkbox"/> 594@osl147.local		Gateway	H323
<input type="checkbox"/> 594@osl147.local		Gateway	H323
<input type="checkbox"/> C60 osl147 Instructor		Endpoint	H323
<input type="checkbox"/> mcu8510@osl147.local		SIP UA	SIP
<input type="checkbox"/> mcu8510@osl147.local	5919	MCU	H323
<input type="checkbox"/> multiway@osl147.local		SIP UA	SIP

- A. 2345
- B. 2345#
- C. 5919*2345
- D. 5919*2345#

Correct Answer: D

QUESTION 7

An engineer wants to stream Cisco TelePresence high-definition video to another location. The stream must be connected to an HDMI input on a display. Which two components, at minimum, are required to provide this functionality? (Choose two.)



- A. Cisco Media Experience Engine 3500
- B. Cisco TelePresence Content Server
- C. Cisco Digital Media Player
- D. Cisco Digital Media Manager
- E. Cisco TelePresence Server

Correct Answer: BC

security, and management specifications for the Cisco TelePresence Content Server.

Table 2. Product Specifications

Product compatibility	<ul style="list-style-type: none">• Support for recording initiation from all standards-based endpoints
Components	<ul style="list-style-type: none">• Simplified, common format, complete solution for streaming, all in one component
Recording	<ul style="list-style-type: none">• Predefined template-based recording options• Recording flexibility through a built-in web-based template editor• Personal and system recording aliases for ultimate flexibility• Support for automated creation of personal recording aliases• Ability to record presentations or video from a live dual stream (H.264, H.239, or DuoVideo)• Support for H.323 endpoints, multipoint control units (MCUs), gateways, and the Session Initiation Protocol (SIP)• Ability to record up to five simultaneous H.323 or SIP video calls• Ability to receive calls at up to 4 Mbps, up to 1080p high-definition (HD) resolution for the main camera and for the second input source• Ability for calls to include main video or audio and H.264, H.239, or DuoVideo• Transcoding of recorded calls into streaming and downloadable file formats, including Windows Media, Flash, and MPEG4 formats• Recording of every call directly to disk for "offline" transcoding after the call completes• Optional record start countdown• Record PIN-protected MCU Conferences• Personal sandbox for safe working on recorded content before publishing• Optional automated email notifications to content owners on completion of recording• Recording indicator on Cisco TelePresence MCU calls

Live and on-demand streaming	<ul style="list-style-type: none">• Ability to stream up to two calls (of the total five) live in a single format and size• Native Windows Media Streaming Server is embedded• When integrated with customer-provided Wowza Media Server, the content server streams Flash[®] content.• When integrated with customer-provided Apple Quicktime or Darwin Streaming Servers, the content server streams MPEG4 QuickTime content• Flash and QuickTime Media can be viewed as a progressive download without external streaming servers• Static URLs for live streaming of MPEG-4 for Flash content from a Wowza Media Server
Streaming	<ul style="list-style-type: none">• Live (unicast and multicast)• On demand (unicast)• Native support for streaming Microsoft Windows Media through an embedded Windows Media Server• Support for external streaming servers (Microsoft Windows Media Server, Wowza Media Server, and Apple QuickTime Streaming Server)
Portable devices	<ul style="list-style-type: none">• Support for Apple iPod and Microsoft Zune
Distribution server	<ul style="list-style-type: none">• Support for Apple's Podcast Producer• Support for iTunes U• Support for Cisco MXE 3500 transformation engine• Support for Cisco Show and Share
Content library	<ul style="list-style-type: none">• Download options• Really Simple Syndication (RSS) feed subscription to provide alternate access to content library



Reference: http://video.global-one.by/files/data_sheet_c78-626482.pdf

QUESTION 8

Which three features are supported by Cisco TMSPE? (Choose three.)

- A. Simplified provisioning
- B. LDAP user import
- C. Scheduling via Microsoft Outlook
- D. FindMe
- E. Jabber for Windows
- F. Automatic endpoint upgrades

Correct Answer: ABD

Table 1. Features and Benefits of Cisco TMSPE



Product Feature	Benefits
Large-scale provisioning	<p>Cisco TMSPE simplifies provisioning for up to 100,000 users:</p> <ul style="list-style-type: none"> • Phone books are automatically created for all provisioned users. You can also create a customized phone book for specific user groups • Any phone book or corporate directory from Cisco TMS can be provisioned to any supported device
User Import	<p>Several types of Active Directory (AD) and Lightweight Directory Access Protocol (LDAP) sources are supported for on-demand or automated import and synchronization of groups and users:</p> <ul style="list-style-type: none"> • Standard Microsoft Active Directory • Secure Microsoft Active Directory with Kerberos • Standard LDAP • Secure LDAP with StartTLS <p>The administrator can choose to automatically send the email message containing provisioning information to users as they are imported from Active Directory.</p>
Low-touch provisioning	<p>Cisco TMSPE supports low-touch provisioning for a variety of Cisco TelePresence systems.</p> <p>This support enables rapid provisioning of user devices, avoiding the need for manual configuration by skilled technicians while saving time, labor, and shipping costs when provisioning users and their devices.</p>
CMR provisioning	<ul style="list-style-type: none"> • Create CMR templates and default service-level settings within the TMSPE User Provisioning page • Cisco TMSPE supports automated Active Directory and LDAP import of users for creating entitlement of up to 100,000 CMRs
Product Feature	Benefits
	<ul style="list-style-type: none"> • An automatic administrator-configurable email is sent to auto-imported users to complete the CMR self-provisioning process • Enable instant WebEx for CMR users • The TelePresence User Portal names the meeting room and modifies default conference settings (Host and guest PIN, layout, auto-connected participants, etc.)
Smart Scheduler	<p>The Cisco TMSPE Smart Scheduler allows administrators and self-service end users to create telepresence meetings quickly and easily.</p> <p>The intuitive menus hide many of the technical configuration details (which are available in the traditional TMS Booking interface for advanced users), allowing you to easily schedule the resources you require.</p> <p>With Smart Scheduler you can:</p> <ul style="list-style-type: none"> • Create and edit single and recurrent meetings (Note: Exceptions to a recurrent series are not supported) • Include Cisco TelePresence Systems and WebEx meetings in the same meeting • Allow additional call-in participants to join your meeting • Set a PIN to secure your meeting; meeting attendees must enter the PIN before they can join
FindMe	<ul style="list-style-type: none"> • With FindMe, you can be reached on any device using a single ID • You can define your locations and specify which endpoints are available to you in those locations • You can also specify which endpoints (video and audio only) should ring when someone calls your FindMe ID • FindMe also allows you to specify additional devices to be called if the default devices are busy or not answered • Administrators can configure account IDs for each user, set up location and device templates, and choose whether to add new devices to FindMe automatically on provisioning • You can create FindMe accounts to define forwarding rules for groups such as support desks • The FindMe portal is located on the Cisco TMS Server, where you can log on with your Active Directory credentials • You can access your Cisco TMSPE account settings, see your username and video address (Session Initiation Protocol Uniform Resource Locator [SIP URI]), and change your provisioning password



Reference: http://www.cisco.com/c/en/us/products/collateral/conferencing/telepresence-management-suite-tms/data_sheet_c78-707901.html

QUESTION 9

When connecting to a pan-tilt-zoom camera to a C-Series codec, what type of cable must be used for camera control?

- A. an Ethernet crossover cable (RJ45-to-RJ45)
- B. an Ethernet cable (RJ45-to-RJ45)
- C. a serial cable (DB25-to-DB9)
- D. a VISCA cable (DB9-to-RJ45)

Correct Answer: D

Camera Control port 1 x Camera Control (RS-232) port for power and camera control (pan, tilt, zoom) using the VISCATM* protocol.

Reference: http://www.cisco.com/c/dam/en/us/td/docs/telepresence/endpoint/codec-c-series/physical_interface_guide/codec-c60_physical_interface_guide.pdf

QUESTION 10

An engineer must pull logs from a Cisco EX90 Codec for a Call setup issue. The engineer opens a Telnet session to the codec and enters the log ctx SipPacket debug 9 command. The engineer places a test call, but sees no debugs on the console.

Which action must the engineer take to review the logs?

- A. SSH into the codec to view the logs
- B. Enter the log ctx SipPacket debug all command
- C. Enter the log output on command.
- D. Collect logs from the web interface.

Correct Answer: C

QUESTION 11

Which protocol is used by Cisco Unified Communications Manager and ISR for media resource control?

- A. SCCP
- B. SIP
- C. RTSP



D. Cisco Discovery Protocol

Correct Answer: C

QUESTION 12

An engineer wants to convert analog live video, streaming it across an IP network and displaying it in another location. Which component is required, at minimum, to provide this functionality?

- A. Cisco Digital Media Manager
- B. Cisco Media Experience Engine 3500
- C. Interactive Experience Client
- D. Cisco TelePresence Content Server

Correct Answer: D

[210-065 PDF Dumps](#)

[210-065 Study Guide](#)

[210-065 Braindumps](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.pass4itsure.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 One Year Free Update <p>Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 Money Back Guarantee <p>To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 Security & Privacy <p>We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4itsure, All Rights Reserved.