



4A0-M10^{Q&As}

Nokia 5G Packet Core Architecture

Pass Nokia 4A0-M10 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/4a0-m10.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which of the following actions is performed when an idle UE moves from 5GS to EPS and the N26 interface is used?

- A. UE initiates an Attach procedure and includes an EPS-GUTI derived from its 5G-GUTI.
- B. For any PDU session that supports interworking, the serving SMF provides an SM context that includes mapped EPS bearers to the AMF.
- C. AMF selects an SGW to serve the UE, and then sets up the required S5-U and S5-C GTP tunnels on the selected SGW.
- D. AMF uses the EPS-GUTI derived from the UE 5G-GUTI to discover the MME, and then provides the UE context to the MME.

Correct Answer: C

QUESTION 2

An AMF needs to know when an SMF deregisters with the NRF. Which of the following NRF APIs should the AMF use?

- A. Nnrf_NFManagement_NFUpdate Request
- B. Nnrf_NFDiscovery_NFDiscover Request
- C. Nnrf_NFManagement_NFStatusSubscribe Request
- D. Nnrf_NFManagement_NFDeregister Request

Correct Answer: A

Reference: https://www.etsi.org/deliver/etsi_ts/123500_123599/123502/15.03.00_60/ts_123502v150300p.pdf

QUESTION 3

Which of the following best describes the Secondary Node Addition procedure?

- A. Used to transfer bearer contexts from the master eNB to the secondary gNB.
- B. Used to establish a UE context at the gNB for a UE that supports option 3X.
- C. Used to establish connectivity from the gNB to the EPC.
- D. Used to establish an X2 connection between the eNB and gNB.

Correct Answer: D

**QUESTION 4**

A UE is handed off from gNB1 to gNB2 using an N2-based handover procedure. The source I-UPF is to be relocated and an indirect data forwarding path is to be used. Which of the following statements is TRUE?

- A. AMF decides that an indirect data forwarding path is required and sends an indication to SMF.
- B. gNB2 tunnel info is allocated for the indirect forwarding path and is included in the Handover Request Ack message sent to AMF.
- C. Target I-UPF tunnel info is allocated for the indirect forwarding path and is provided to the UPF PSA.
- D. UPF PSA tunnel info is allocated for the indirect forwarding path and is provided to the source I-UPF.

Correct Answer: A

QUESTION 5

Which of the following does NOT apply to an idle UE in MICO mode?

- A. The UE performs registration updates.
- B. The UE connects to the network to send uplink data.
- C. Power and signaling efficiency is optimized for the UE.
- D. The UE listens and responds to paging.

Correct Answer: D

Reference: <https://blog.3g4g.co.uk/2020/07/mobile-initiated-connection-only-mico.html>

QUESTION 6

Which of the following best describes a UE route selection policy (URSP)?

- A. A URSP is a policy pre-configured in the UE. The UE uses this policy to select a non-3GPP access network and an N3IWF to use in the PLMN.
- B. A URSP is a policy provisioned to AMF by PCF. The AMF uses this policy to select an SMF that can serve a given PDU session for the UE.
- C. A URSP is a policy that can be pre-configured in the UE or provisioned to the UE by PCF. The UE uses this policy to determine how to handle a given application.
- D. A URSP is a policy pre-configured on the SMF. The SMF uses this policy to select a UPF that can serve a given PDU session for the UE.

Correct Answer: C



Reference: <https://itectec.com/spec/6-6-ue-policy-information/>

QUESTION 7

Which of the following is NOT an advantage of the 5GS service-based architecture?

- A. Application programming interfaces (APIs) are used to invoke services.
- B. Service-based interfaces are point-to-point.
- C. The service-based architecture enables flexible addition of new network functions and services.
- D. Service producers are not aware of service consumers.

Correct Answer: C

QUESTION 8

Which of the following is an HTTP method used by an NF service consumer to create a new resource at an NF service producer when the resource URI is selected by the consumer?

- A. POST
- B. PUT
- C. PATCH
- D. UPDATE

Correct Answer: B

Reference: https://www.tech-invite.com/3m29/toc/tinv-3gpp-29-501_c.html

QUESTION 9

Which Nokia product is used for the AMF in 5GS?

- A. Cloud Mobility Manager
- B. Cloud Mobile Gateway
- C. Network Resource Discovery
- D. Smart Plan Suite

Correct Answer: A

Reference: <https://www.nokia.com/networks/products/cloud-mobility-manager/>



QUESTION 10

Which of the following statements about network slice selection assistance information (NSSAI) is FALSE?

- A. Allowed NSSAI is a set of slices provided to UE by AMF during UE registration procedure.
- B. Requested NSSAI is a set of slices provided by UE to the network and contains values from serving PLMN.
- C. Subscribed NSSAI is a set of slices specified in the UE subscription data and contains only home PLMN values.
- D. Configured NSSAI is a set of slices configured on the AMF and contains slices supported per tracking area.

Correct Answer: A

[Latest 4A0-M10 Dumps](#)

[4A0-M10 Study Guide](#)

[4A0-M10 Braindumps](#)