Exam : 642-356

Title : Cisco Storage Networking Solutions Support Specialist(CSSSS)

Version (

MNN

DEMO

1. Which command would you use to determine if device aliases in VSAN 5 are configured for fabric-wide distribution?

A. show zoneset name alias vsan 5

B. show cfs application name device-alias

C. show fcalias distribution vsan 5

D. show vsan 5 device-alias status Answer: B

2. The MDS 9000 family switches use what three technologies to protect against unauthorized management access? (Choose three.)

A. SNMPv3

B. SSH C.

RBAC D.

RMON E.

SES

F. WEBM Answer: ABC

- 3. What is a benefit of enhanced zoning?
- A. fabric locked during configuration changes
- B. larger zoning database size
- C. database rollback in case of failure
- D. zones allowed to span VSANs Answer: A
- 4. Which two of these environments suggest the use of FCIP Write Acceleration? (Choose two.)
- A. remote tape backup
- B. PortChannel links between sites
- C. applications that support multiple outstanding I/Os

Get Latest & Actual IT Exam Dumps with VCE and PDF from Pass4itSure. https://www.Pass4itSure.com

D. fast network with minimal delays

E. DWDM links Answer: BC

5. Which three of the following are possible reasons why a line card module does not come online? (Choose three.)

A. Port indexes have been taken offline.

B. Available port indexes are noncontiguous.

C. Not enough power is available in the chassis.

D. An invalid interoperability mode has been configured.

E. Unsupported SFPs have been installed.

F. Not enough port indexes are available. Answer: BCF

6. Refer to the exhibit. Which two options from the Tools menu would you select to verify connectivity and latency to a Fibre Channel end device? (Choose two.)

Z.

🚭 Febric Nanager 1.3(2a)		ft. In your
File Zone Edit View Tools	Parformanice Server Holp 21 🗐 🔛 🕂 🐨 🔒 🕱 🎧	
Prese: 10.0.1.18 Pri All Vanne 9 USAN0001 9 USAN0100 Pri VSAN0200	Spritches St.s houts Storage	All Ysans
	Lophy Name P Address VWW Staus	Switch Health
	mite 2216 12 a 10,10 11 b Cisco 20,00,00 0b total0 6a c0 Moste 1 mite 2216 16 a 10,10 1 7 Cisco 20,00,00 05 30,00 5a 1a ok mite 2216 2a *** Cisco 20,00,00 05 30,00 5a 1a ok	Fabric Configuration
	mdr59(16_2b 16_10.2.29 Carpo 20.00.00.05.30.00.50 te ;08	End to End Connectivity
		Ping
		Traceroute
		Device Manager
		Command Line Interface Show Tech Support
E Logical Physical	Da 1 200 A Everts	

A. Switch Health

B. Fabric Configuration

C. End to End Connectivity

D. Ping

E. Device Manager Answer: CD

7. During initial switch configuration, the administrator elects to enable full zoneset distribution. What is the impact of this choice during zoneset activation?

A. only the active zoneset is distributed to all switches in the fabric

B. both the full zone database and active zoneset are distributed to all switches in the fabric

C. both FCID and WWN information are distributed to all switches in the fabric

D. only the full zone database is distributed to all switches in the fabric Answer: B

8. You are asked to review the running configuration of a switch that a junior administrator has prepared to be placed in a heterogeneous SAN environment. This environment includes three different brands of Fibre Channel switches. In this particular environment, only VSAN 1 is being used.

Which of these attributes suggests that the switch has been incorrectly configured?

A. A static domain ID has been set to 0x21.

B. The src-dst-ox load balancing has been selected.

C. Interop mode 1 has been selected.

D. FCC has been enabled.

Answer: A

9. What two commands must be executed on an MDS 9000 family switch in order to change a dynamically assigned Domain ID 5 to a static Domain ID 10 for VSAN 10? Choose two.

- A. switch(config-if)# shut fcdomain 5
- B. switch(config-if)# no shut fcdomain 10
- C. switch(config)# fcdomain domain 10
- D. switch(config)# fcdomain domain 10 static vsan 10
- E. switch(config)# fcdomain restart vsan 10

F. switch(config)# fcdomain restart disruptive vsan 10 Answer: DF

10. When configuring FCIP, packet fragmentation should be avoided in order to achieve optimal throughput. Fragmentation can be avoided by knowing which of the following?

A. MTU of the source IP interface

www.Passhitsure.com

Trying our product !

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- * Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:

Submit A Ticket

One Year Free Update

Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email. Money Back Guarantee

To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase. We resp use Mc.

Security & Privacy

e. C

> We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.

Guarantee & Policy | Privacy & Policy | Terms & Conditions

100%

Any charges made through this site will appear as Global Simulators Limited. All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.

Get Latest & Actual IT Exam Dumps with VCE and PDF from Pass4itSure. https://www.Pass4itSure.com