Exam : 642-444

Title : IP Telephony Exam (CIPT)

Version : Demo

- 1. Which four characteristics would typically be used to define a device pool? (Choose four.)
- A. geographic proximity B. common use of codecs
- C. common MOH source
- D. common device type
- E. common class of service
- F. common calling search spaces for auto-registration

Answer: ABCF

- 2. What method of Call Admission Control (CAC) is used for centralized call processing?
- A. locations
- B. regions
- C. gatekeeper
- D. H.225
- E. gateway
- F. H.323

Answer: A

3. Two options exist for adding a gatekeeper-controlled trunk to support gatekeeper call administration control. Which two of the following options could be selected to configure the trunk type as shown in the exhibit? (Choose two.)



- A. H.225 Trunk (Gatekeeper Controlled)
- B. Inter-Cluster Trunk (Gatekeeper Controlled)
- C. Intra-Cluster Trunk (Gatekeeper Controlled)
- D. H.323 Trunk (Gatekeeper Controlled)
- E. H.245 Trunk (Gatekeeper Controlled)

Answer: AB

4. Refer to the exhibit. What CSS should be assigned to a phone in the Phones partition to block calls to International numbers while allowing all other calls?

```
Partition - Phones
Partition = Service
  Route Pattern XII
Partition = Local
   Route Pattern XII
   Route Pattern 9.9
Partition - LongDistance
  Route Pattern XII
  Route Pattern 9.[2-9]XXXXXX
  Poute Pattern 9.1[2-9]XX[2-9]XXXXXX
Partition = International
  Route Pattern 9.011'
CSS A
  Phones
  Service
CSS B
  Service
  Local
  LongDistance
  LongDistance
CSS D
   Phones
  LongDistance
```

A. CSS A B.

CSS B C.

CSS C D.

CSS D

Answer: D

5. An IP phone user has dialed "15152412232". Which of the following route patterns will be used?

A. 1515[^0-1]4[123]+

B. 1515[^0-2]4[012]+ C.

1515[^0-1]41[2232] D.

1515[^0-2]412[012]+

E. will not match any of these patterns

Answer: A

6.	Which three	of the following	g can be	assigned a	partition? ((Choose three.)	

- A. gateway
- B. directory number
- C. translation pattern
- D. route pattern
- E. IP phone

Answer: BCD

- 7. A dial plan uses six-digit numbers where the first two digits are an access code and the last four digits are an extension. Access codes must begin with 7 or 8 and the second digit cannot be 0, 1, 5, or 9. Which two route patterns will support this dial-plan requirement? (Choose two.)
- A. [78][2-4,6-8].XXXX
- B. [7-8][^0159].XXXX
- C. [^0-6,9][2-4,6-8].XXXX
- D. [^0-69][2-4678].XXXX
- E. [^78][^234678].XXXX

Answer: BD

- 8. When a phone needs a conference resource, which of the following Cisco CallManager objects is queried first?
- A. media resource device list
- B. media resource pool
- C. media resource group list
- D. media resource group

Answer: C

- 9. Which multiple line appearance parameter sets a number of calls per line beyond which all incoming calls are forwarded?
- A. Maximum Number of Calls
- B. Call Forward Busy

- C. No Answer Ring Duration
- D. Busy Trigger

Answer: D

- 10. Which two of these options can you use to prevent toll fraud? (Choose two.)
- A. Call Forward CSS
- B. IPSec encryption
- C. MLA
- D. forced authentication codes
- E. Call Transfer CSS

Answer: AD

- 11. Which two items can a route pattern be assigned? (Choose two.)
- A. gatekeepers that do not perform gateway functions
- B. route groups that contain one or more route filters
- C. gateways
- D. route lists that contain one or more route groups
- E. route filters
- F. route lists that contain one or more route filters

Answer: CD

- 12. You are working with a customer to deploy a pilot network to test how Cisco CallManager interoperates with SIP. Which two components need to be deployed for Cisco CallManager to interoperate with the SIP portion of the network? (Choose two.)
- A. Registrar server
- B. SIP to H.323 trunk
- C. SIP trunk
- D. proxy server
- E. redirect server
- F. location database

Answer: CD

13. A Cisco CallManager cluster contains one publisher and four subscribers. If the publisher is

unavailable, which three of these statements are true? (Choose three.)

A. The Microsoft SQL Server 2000 database automatically locks.

B. New Cisco CallManager devices can be configured.

C. The Microsoft SQL Server 2000 will save configuration changes on subscribers to be uploaded to the

publisher when available.

D. CDR collection is temporarily suspended on subscribers.

E. All IP telephony devices continue to operate.

F. Available Cisco CallManagers work from the local backup database.

Answer: AEF

14. Which three of these options correctly describe the role of a subscriber in a Cisco CallManager cluster?

(Choose three.)

A. replicates database to other Cisco CallManager servers

B. maintains read-only copies of the configuration database

C. processes IP telephony calls

D. collects CDRs

E. can have only one in a Cisco CallManager cluster

F. maintains writeable copy of the configuration database

Answer: BCD

15. Which two of these services should be disabled during post-installation of Cisco CallManager to

prevent potential intruders from finding server vulnerabilities? (Choose two.)

A. Distributed File System

B. FTP Publishing Service

C. SSL Security Service

D. Forward Publishing Service

E. SRTP service

Instant Download PDF And VCE 100% Passing Guarantee 100% Money Back Guarantee

F. SRCP service

Answer: AB

16. Which two of these events describe the relationship of an IP Phone to its secondary Cisco

CallManager? (Choose two.)

A. IP Phone sends a TCP keepalive message every 30 seconds.

B. IP Phone sends a TCP keepalive message every 60 seconds.

C. IP Phone sends a TCP connect message.

D. IP Phone registers with secondary when primary is unavailable.

E. IP Phone registers with primary when secondary is unavailable.

F. IP Phone registers with all CallManagers initially including secondary.

Answer: CD

17. An auto parts retailer would like their service counter representatives to be able to assist both walk-up

customers and telephone customers. Each store has six service counter representatives.

Which call distribution algorithm will allow each service counter representative to provide the best

customer service?

A. Top Down

B. Circular

C. Longest Idle Time

D. Broadcast

Answer: D

18. An auto parts retailer would like their service counter representatives to assist both walk-up customers

and telephone customers. Each store has six service counter representatives. Walk-up customers

frequently engage all the counter representatives and management is concerned that telephone customer

business is being lost.

From the list below, choose the appropriate call distribution algorithm and the appropriate call forwarding

treatment which will allow each store to provide the best customer service. (Choose two.)

A. When hunting is exhausted, apply CFB and CFNA to the DN for the warehouse order puller.

B. There is no need to configure CFB or CFNA; when hunting is exhausted, the call will automatically be routed to the warehouse order puller.

C. Top Down

D. Circular

E. Longest Idle Time

F. Broadcast

Answer: AF

19. You are working with a customer to develop the methodology to secure IP Phones at their new research facility. They will be providing IP Phones in their lobby for vendor and guest use. Which two of these IP Phone hardening methods should be applied to these devices? (Choose two.)

A. Enable GARP.

B. Disable PC port on phone.

C. Use signed IP phone firmware.

D. Disable the Directory button.

E. Disable the Services button on the IP phone.

Answer: BC

20. Which three options can you use to assign a softkey template? (Choose three.)

A. Device > Phone Configuration

B. Device > Device Settings > Device Profile

C. Service > Service Parameters

D. System > Device Defaults Configuration

E. System > Device Pool Configuration

F. System > Enterprise Parameters

Answer: ABE

21. An MRGL is used to control access to which three of these resources? (Choose three.)

A. MoH

B. Cisco IP Phone Services

- C. softkey templates
- D. annunciator
- E. MTP
- F. CTI applications

Answer: ADE

- 22. Which of these options will prevent a device from being able to initiate conferences?
- A. Exclude the conference media resource partitions from the CSS.
- B. Exclude the conference media resources from all MRGs.
- C. Place all conference media resources in MRGs and exclude these MRGs from the MRGL.
- D. Remove the default MRGL from the device pool.

Answer: C

- 23. Which four of these items can be obtained from Call Detail Records? (Choose four.)
- A. quality of service information
- B. call duration
- C. Client Matter Codes
- D. circuit utilization
- E. blocked call attempts
- F. malicious call information

Answer: ABCF

- 24. How is a backup target changed to a backup server?
- A. Modify the BARS service parameter from Target to Server.
- B. Uninstall BARS and reinstall as a backup server.
- C. Use BARS administration to change from Target to Server.
- D. Use BARS administration to delete the destination target.

Answer: B


25. A user reports poor quality on voice calls and is instructed to select the QRT softkey. How can you

access the information generated by this call?

- A. use Tools\QRT Viewer under the Cisco CallManager Serviceability page
- B. use the perfmon counter application under Administrative Tools
- C. use the System\Real-time Monitor Tool under Cisco CallManager Administration
- D. use the QRT plug-in on the PC of an administrator

Answer: A

26. What will this translation pattern configuration accomplish?



- A. allows the display of the calling number
- B. blocks the display of the calling number
- C. honors the presentation display of the caller
- D. does not change the calling line ID presentation

Answer: B

27. Which two of these tools can be used to reestablish a Cisco CallManager cluster SQL subscription? (Choose two.)

A. DNA B.

RTMT

- C. DBLHelper
- D. SQL Server Service Manager
- E. SQL Server Enterprise Manager

Answer: CE

28. At Benjamin Church Spyware Co., the Cisco CallManager administrator selects the NANP and then adds the 9.@ route pattern with the filter SERVICE EXISTS.

Which pattern will be added?

- A. 9[2-9]11
- B. 9[2-9]xx xxxx
- C. 9 011 3[0-469]!
- D. 9 1 900 [2-9]xx xxxx
- E. 9[2-9]xx [2-9]xx xxxx

Answer: A

- 29. What are Cisco CallManager Regions used for?
- A. Specify the bandwidth used for audio and video calls.
- B. Define the time zones for devices connected to the Cisco CallManager.
- C. Provide alternate call routing when the primary call path is unavailable.
- D. Implement call admission control in a centralized call processing deployment.
- E. Assign directory numbers to devices as they connect to the IP telephony network.

Answer: A

- 30. Which configuration parameter may need to be adjusted when the Region setting is changed?
- A. Region
- B. Location

- C. Device Pool
- D. AAR Group
- E. Class of Control

Answer: B

Trying our product!

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:





Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.