



642-980^{Q&As}

Troubleshooting Cisco Data Center Unified Fabric

Pass Cisco 642-980 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/642-980.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

An administrator wants to combine the advantages of a trunking F port and an F port channel.

Which command on a Cisco MDS switch should be used to enable this?

- A. enable port-channel
- B. feature trunking-fport
- C. feature fport-channel-trunk
- D. port-channel trunk
- E. feature fport-trunk

Correct Answer: C

QUESTION 2

Refer to the exhibit.

```
switch# sh int fc2/7
fc2/7 is down (NPV upstream port not available)
Hardware is Fibre Channel, SFP is short wave laser w/o OFC (SN)
Port WWN is 20:47:00:0d:ec:a4:3b:80
Admin port mode is F, trunk mode is off
snmp link state traps are enabled
Port vsan is 99
Receive data field Size is 2112

switch# show vsan membership
vsan 1 interfaces:
fc2/1 fc2/2 fc2/3 fc2/4
fc2/5 fc2/6 san-port-channel 200
vsan 99 interfaces:
fc2/7 fc2/8
```



The server port connected to the NPV edge switch does not come online. Which action should fix the problem?

- A. Move the NP ports on the NPV edge and the F ports on the NPIV into the same VSAN 99.
- B. Move the NP ports on the NPV edge and the F ports on the NPIV in the default VSAN 1.
- C. Move all the ports into VLAN 1.
- D. Move all the ports into VSAN 99.



E. Move all the ports into VLAN 99.

Correct Answer: A

QUESTION 3

Which two describe the correct requirements for non-disruptive IOS ISSU on Cisco Nexus 7000 Series Switches? (Choose two.)

- A. updated kickstart and system images must be staged in bootflash on single-supervisor switches
- B. updated kickstart and system images must be staged in bootflash on dual-supervisor switches
- C. low version skew
- D. dual supervisors
- E. clock synchronization

Correct Answer: CD

QUESTION 4

What are the two most common causes of the "SFP validation failed" error on an interface when you attempt to connect a Cisco Nexus 2148T Fabric Extender to a Cisco Nexus 5548UP Switch? (Choose two.)

- A. The port must be in switchport monitor mode.
- B. It is a hardware limitation of the Cisco Nexus 2148T.
- C. The wrong speed is configured on the interface.
- D. The incorrect license has been applied on the Cisco Nexus 5548UP.
- E. The wrong switchport mode is configured on the interface.

Correct Answer: CE

QUESTION 5

What are three reasons that could cause fabric merge problems in a Cisco SAN? (Choose three.)

- A. Failure occurs when a switch supports more than 2000 zones per VSAN but its neighbor does not.
- B. All devices are in the same VSAN.
- C. The merged fabrics contain inconsistent data that could not be merged.
- D. Both host and storage are logged in to the same SAN.
- E. Small configurations may wipe out the large configurations.



F. The VSAN database is error-disabled.

Correct Answer: ACE

QUESTION 6

What are three situations that may cause an ISSU failure? (Choose three.)

- A. A module is removed while the upgrade is in progress.
- B. A proper ISSU license is not in place.
- C. The device has a power disruption while the upgrade is in progress.
- D. A line card is in a failure state.
- E. The specified system and kickstart images are not compatible.
- F. The management interface is not in the correct VRF.
- G. The secondary supervisor is not installed.
- H. The redundancy force-switchover command was used during the ISSU.

Correct Answer: CDE

QUESTION 7

To ensure that DCBX can be run on a switch, which other feature must be enabled?

- A. Cisco Discovery Protocol
- B. LLDP
- C. Fibre Channel
- D. IEEE 802.1ad

Correct Answer: B

QUESTION 8

The traffic across your port channels seems to be favoring one link over the other. How can you adjust the load-balancing policy to include source and destination MAC addresses, IP address, and TCP port?

- A. `kc5010-1(config-if)# port-channel load-balance ethernet source-dest-port`
- B. `kc5010-1(config-if)# port-channel load-balance ethernet source-dest mac ip port`
- C. `kc5010-1(config)# port-channel load-balance ethernet source-dest-port`



D. kcdc-5010-1(config)# port-channel load-balance ethernet source-dest mac ip port

Correct Answer: C

QUESTION 9


Refer to the exhibit.

```
switch# show npv status

npiv is enabled

External Interfaces:
=====
Interface: fc1/1, VSAN: 1, FCID: 0x110000, State: Failed(Mismatch in VSAN for this
upstream port)

Number of External Interfaces: 1
```



When suspending or deleting VSANs, which three statements are true? (Choose three.)

- A. You can delete only one VSAN at a time.
- B. You must wait 60 seconds after you enter the vsan suspend command before you enter another command.
- C. You must wait 120 seconds after you enter the vsan suspend command before you enter another command.
- D. You can unsuspend only one VSAN at a time.
- E. You can delete multiple VSANs as long as they are in the same domain.
- F. You can delete multiple VSANs as long as they are in the same zone.

Correct Answer: ABD

QUESTION 10

On a Cisco Nexus 5500 Series Switch, the VFC is stuck in the initializing state. Which QoS statements must be configured for FCoE to operate?

- A. system qos service-policy type qos input fcoe-default-in-policy service-policy type queuing input fcoe-default-in-policy service-policy type queuing output fcoe-default-out-policy service-policy type network-qos fcoe-default-nq-policy
- B. system qos service-policy type qos input fcoe-default-in-policy service-policy type queuing input fcoe-default-in-policy service-policy type qos input default-in-policy service-policy type network-qos default-nq-policy
- C. system qos service-policy type qos input default-in-policy service-policy type queuing input default-in-policy service-policy type queuing output default-out-policy service-policy type network-qos default-nq-policy
- D. system qos service-policy type qos input default-in-policy service-policy type queuing input default-in-policy service-policy type queuing output fcoe-default-out-policy service-policy type network-qos fcoe-default-nq-policy



Correct Answer: A

QUESTION 11


Which three statements are true about using the debug command to resolve an HSRP issue on the Cisco Nexus platform? (Choose three.)

- A. The debug command should be allowed to run for at least an hour.
- B. The administrator can log debug messages to a special log file to avoid flooding the console.
- C. Open a second Telnet or SSH session before you enter any debug commands so that if the debug session overwhelms the console, you can stop the message output.
- D. Use the debug command only under the guidance of Cisco Technical Support.
- E. Use the Ethalyzer remote interface command to capture packets.
- F. The debug peer-gateway command should be used to isolate the problem.

Correct Answer: BCD

QUESTION 12

Refer to the exhibit.



An administrator sets up a FabricPath network. The administrator tries to ping between two SVI interfaces on the leaf switches 10 and 20, but it fails. What caused the pings to fail?

- A. Switches S10 and S20 do not have F2 modules.
- B. The vPC peer gateway must be enabled on switches S10 and S20.
- C. Switches S1, S2, and S3 should be interconnected directly.
- D. VLAN 10 is not enabled on the spine switches (S1, S2, and S3).



E. Layer 3 over a vPC+ peer link is not supported.

Correct Answer: D

[642-980 Practice Test](#)

[642-980 Exam Questions](#)

[642-980 Braindumps](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.pass4itsure.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4itsure, All Rights Reserved.