
Exam : 642-993

Title : Data Center Unified

Computing Systems Design

(DCUCD)

Version : DEMO

1. Which of the following would be considered a Cisco Unified Computing technical design criteria?
--

- A. Increase the number of servers in the data center.
- B. Decrease security requirements.
- C. Simplify the Data Center architecture.
- D. Reduce power costs while maintaining or increasing compute capacity.

Answer: C

- 2. Which three business pressures are most typically faced by data centers? (Choose three.)
- A. language barriers
- B. government regulation and compliance
- C. SLA metrics
- D. global availability
- E. technology silos

Answer: B,C,D

- 3. Which two physical security concerns would most likely be considered first when planning a data center installation? (Choose two.)
- A. ventilation
- B. alarm systems
- C. raised flooring
- D. fire suppression systems

Answer: B,D

4. Which condition is prevented by the use of the "Combined" power redundancy mode in the Nexus 7000?

Instant Download PDF And VCE 100% Passing Guarantee 100% Money Back Guarantee A. one PSU failure B. lack of redundancy C. one input circuit failure D. one PSU or one input circuit failure Answer: B 5. Which statement is true regarding UCS ports dedicated as external LAN device uplinks? A. Ports carry VLAN traffic only B. Ports are configured as ISL trunks C. Spanning tree must be enabled on these ports D. Ports are configured as access ports Answer: A 6. Which three components are included in Cisco Business Advantage Data Center Architecture? (Choose three.) A. unified I/O B. virtualization C. Security Manage D. consolidation E. Desktop Consolidator

7. What is the purpose of the L1 and L2 ports on the Cisco UCS 6100 and 6200 Series Fabric Interconnect switches when running in a cluster with another fabric interconnect?

A. support LACP

Answer: A,B,D

- Instant Download B. provide high-availability services C. used for out-of-band management D. centralized management port Answer: B 8. Which is a characteristic of the end-host-mode? A. It offers no redundancy. B. It participates in STP. C. It participates in network control data plan. D. UCS appears to the external LAN as an end station with many adapters. Answer: D 9. What is the primary purpose of NPIV? A. It is a switch-based solution with a reduction in overhead. B. Virtual server interfaces can be created within an Cisco MDS switch. C. Virtual machines can bypass the hypervisor and access a LUN directly. D. Multiple virtual applications can share a single switch port while maintaining their identity. Answer: D 10. What is the purpose of a VSAN in a Cisco Data Center network? A. to share the zoning across other configured VSANs B. to provide distributed service within the SAN fabric

- C. to advertise the existence of LUNs across the storage area management fabric
- D. to facilitate logical end-to-end separation within a single physical storage infrastructure

Answer: D



Trying our product!

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:





Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.