

# 100% Money Back Guarantee

**Vendor:** IBM

**Exam Code:** C4120-783

**Exam Name:** IBM PureFlex Technical Support V2

**Version:** Demo

[www.Pass4itSure.com](https://www.Pass4itSure.com)

**QUESTION NO: 1**

Which of the following virtualization products is required to create logical partitions on the p460 compute node?

- A. HMC
- B. KVM
- C. IVM
- D. PowerVM

**Answer: D**

**Explanation:**

**QUESTION NO: 2**

Design criteria dictates the use of SAN pass-thru now and the ability to upgrade to full fabric capability later. Which of the following is the most cost effective way to accomplish this?

- A. Select the 8Gb SAN Switch module now and enable full fabric functionality later
- B. Select the 8Gb SAN Pass-thru module now and enable full fabric functionality later
- C. Select the 8Gb SAN Switch module now and switch to Brocade interoperability mode later
- D. Select the 8Gb SAN Pass-thru module now and convert to full functionality through activation codes later

**Answer: A**

**Explanation:**

**QUESTION NO: 3**

Which of the following features is only available with the Flex System Manager Advanced license?

- A. Image Management
- B. Fabric Management
- C. Storage Management
- D. Virtualization Management

**Answer: A**

**Explanation:**

**QUESTION NO: 4**

An IBM customer is concerned with transferring their Power AIX workloads to PureFlex. Which of the following tools can predict the performance of AIX workloads on PureFlex?

- A. Power Configurator
- B. System Planning Tool
- C. Live Partition Mobility
- D. Systems Workload Estimator

**Answer: D**

**Explanation:**

**QUESTION NO: 5**

A PureFlex prospect has CLARiiON CX4-240, AMS 2100, HP 8200, and Dell EqualLogic. They wish to consolidate by virtualizing with IBM Flex Systems V7000 Storage Node. Which of the following will be an issue?

- A. HP 8200
- B. AMS 2100
- C. Dell EqualLogic
- D. CLARiiON CX4-240

**Answer: C**

**Explanation:**

**QUESTION NO: 6**

A customer wants to purchase a PureFlex solution with 10Gb network interfaces on a 32-core Power node. Each virtual machine has a critical function and unplanned down time must be avoided. Which of the following provides the most resilient solution?

- A. p260 server with two 10Gb chassis switches
- B. p460 server with two 10Gb chassis switches
- C. p260 server with one 10Gb chassis switch with the first switch activation upgrade
- D. p460 server with one 10Gb chassis switch with the first switch activation upgrade

**Answer: B**

**Explanation:**

**QUESTION NO: 7**

A prospect requires NIC teaming with redundant switches. The prospect is concerned about what the default IBM PureFlex Lab Services implementation includes. Which of the following is the minimum offering which includes setup of NIC teaming with redundant switches?

- A. Flex System
- B. PureFlex Express
- C. PureFlex Enterprise
- D. PureData for Analytics

**Answer: C**

**Explanation:**

**QUESTION NO: 8**

There are a number of different ways to access a node console for Power and x86 compute nodes. Which of the following is a supported method for this requirement?

- A. Physically plugging in a Console Breakout Cable
- B. Connection to the FSM management interface via serial port
- C. Connect remotely into the serial management port of the CMM
- D. Connect via browser to each IMM2 on a node and invoke a remote PuTTY session to that node

**Answer: A**

**Explanation:**

**QUESTION NO: 9**

A customer has purchased a PureFlex Express system and requires additional services for their POWER7 node with IBM i. Which of the following addresses this need?

- A. Add additional SWMA
- B. Add IBM Lab Services Days in e-config
- C. Add separate IBM Lab Services contract
- D. Add services to the maintenance contract

**Answer: C**

**Explanation:**

**QUESTION NO: 10**

A prospect is considering a single chassis PureFlex System Express with two compute nodes. Which of the following business pressures could be reduced with the installation of PureFlex?

- A. Employing more cost effective open products
- B. Deploying applications faster for quicker time to market
- C. Reduce cost management of zBX, System x, and Power servers
- D. Top of Rack (TOR) Switches flatten the network to reduce management costs

**Answer: B**

**Explanation:**

**QUESTION NO: 11**

How are the management networks of two PureFlex chassis interconnected?

- A. CMM external ports
- B. Interconnect nodes
- C. Front and rear flex cables
- D. Top of rack InfiniBand switch

**Answer: A**

**Explanation:**

**QUESTION NO: 12**

A customer has a legacy x86 deployment on physical servers. What benefit does VMware offer to preserve legacy workloads?

- A. Allows use of Active Memory Expansion in VMware
- B. Allows use of IBM Storage Management Console for VMware vCenter plug-in
- C. User-controlled CPU frequencies allow slower legacy hardware timings to be preserved
- D. Select operating systems not natively supported on the new hardware are supported under VMware

Answer: D Explanation:

**QUESTION NO: 13**

How are the management networks of two PureFlex chassis interconnected?

- A. Interconnect nodes
- B. CMM external ports
- C. Front and rear flex cables
- D. Top of rack InfiniBand switch

**Answer: C**

**Explanation:**

**QUESTION NO: 14**

A PureFlex technical specialist is discussing the PureFlex family with a prospective customer. They are concerned about available chassis space. Which PureFlex compute node option is full width?

- A. x240
- B. p260
- C. x220
- D. p460

**Answer: D**

**Explanation:**

**QUESTION NO: 15**

A customer is considering a PureFlex Standard solution. Which of the following is included in the five day IBM Lab Services engagement?

- A. Demonstrate Live Application Mobility
- B. Implement System Server Pools with VMControl
- C. Create an image repository for use with VMControl
- D. Use vCenter to create a cluster of virtual servers

**Answer: C**

**Explanation:**

**QUESTION NO: 16**

Each x86 node can be individually connected to a portable console, keyboard, and mouse. This is often referred to as "crash cart" management capability. Which of the following is required to perform this connection?

- A. Physically plugging a KVM cable to the CMM
- B. Physically plugging in a console breakout cable to the compute node
- C. Physically plugging in a serial cable to the diagnostic port of the CMM
- D. Physically plugging in a proprietary male 9 pin cable to the compute node

**Answer: B**

**Explanation:**

**QUESTION NO: 17**

A customer has an application which requires access to more than two separate networks and has a limited number of physical ports to support the environment. They plan on implementing Virtual NIC interface. Which of the following meets these requirements?

- A. 802.1Q relies on data center bridging
- B. 802.1Q allows for NIC teaming providing additional ports
- C. 802.1Q controls the quality of service which can be used to prioritize traffic to those applications
- D. 802.1Q VLAN tagging is used to divide one physical Ethernet interface into several logical interfaces that belong to different VLANs

**Answer: D**

**Explanation:**

**QUESTION NO: 18**

A prospect requires NIC teaming with redundant switches. The prospect is concerned about what the default IBM PureFlex Lab Services implementation includes. Which of the following is the minimum offering which includes setup of NIC teaming with redundant switches?

- A. Flex System
- B. PureFlex Express
- C. PureFlex Standard
- D. PureFlex Enterprise

**Answer: D**

**Explanation:**

**QUESTION NO: 19**

Which IEEE networking standard does PowerVM use for VLAN tagging in the hypervisor?

- A. 802.1
- B. 802.4
- C. 802.3Q
- D. 802.1Q

**Answer: D**

**Explanation:**

**QUESTION NO: 20**

A customer is considering PureFlex x86 nodes for an application that requires multiple virtual network interfaces and guaranteed bandwidth. The customer has a strict governance policy and demarcation between server and network administrators. As such, all virtual network and bandwidth configuration is handled by the network administrator. Which of the following adapter modes meets the customer requirements?

- A. Adapter has pNIC Mode Enabled
- B. Adapter has virtual LANs (VLANs) Enabled
- C. Adapter has Virtual Fabric Mode (VNIC1) Enabled
- D. Adapter has Switch Independent Mode (VNIC2) Enabled

**Answer: C**

**Explanation:**



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

# Trying our product !


- ★ **100%** Guaranteed Success
- ★ **100%** Money Back Guarantee
- ★ **365 Days** Free Update
- ★ **Instant Download** After Purchase
- ★ **24x7** Customer Support
- ★ Average **99.9%** Success Rate
- ★ More than **69,000** Satisfied Customers Worldwide
- ★ Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

## Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <b>One Year Free Update</b> <p>Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <b>Money Back Guarantee</b> <p>To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <b>Security &amp; Privacy</b> <p>We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information &amp; peace of mind.</p>
---	---	--

## Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.