C9510-842^{Q&As}

Rational Functional Tester for Java

Pass IBM C9510-842 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/c9510-842.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

How do you stop recording?

A. click the Stop Recording button on the recording toolbar

B. end the application under test

C. close RFT

D. close the recording monitor

Correct Answer: A

QUESTION 2

Which three statements are true about HelperSuper classes? (Choose three.)

A. Scripts can share Helper Superclasses.

B. Scripts cannot share Helper Superclasses.

C. Scripts can inherit from multiple Helper Superclasses.

D. Scripts can inherit from a Helper Superclass that resides in a .jar file.

Correct Answer: ACD

QUESTION 3

A script needs to perform an action on an object. One of the recognition properties of the object is the .url property. The URL is dynamic. At recording time, the URL was http://www-3.ibm.com. However, it can vary every time the script is

played back. In particular, the portion of the .url property that is subject to change is the digits that appears after the dash.

Which regular expression will match the value of the .url property regardless of the numer of digits between the - and the .?

Note: The regular expression should NOT match the .url property if no digits appear after the dash (as in www-.ibm.com).

A. www-*\.ibm\.com

B. www-{num}?\.ibm\.com

C. www-{num}+\.ibm\.com

D. www-[0-9]*\.ibm\.com

E. www-[0-9]\.ibm\.com

Correct Answer: C

QUESTION 4

What are the default values for retry interval and maximum retry time?

A. 2 second retry interval, 20 seconds maximum retry time

B. 5 second retry interval, 30 seconds maximum retry time

C. 1 second retry interval, 5 seconds maximum retry time

D. 3 second retry interval, 15 seconds maximum retry time

Correct Answer: A

QUESTION 5

Functional Tester allows you to import an external datapool from which of the following ? (Choose three.)

A. an external .csv file

B. another Functional Tester datapool

C. an existing TestManager datapool

D. an access (.mdb) file

Correct Answer: ABC

QUESTION 6

What should the tester open to view Test Objects, Main Data Area and Recognition Data?

A. the test script

B. the test comparator

C. the object map

D. the log viewer

Correct Answer: B

QUESTION 7

Out of the box, what are the different options for logging RFT tests?

A. HTML, text, custom, TestManager, and none

B. HTML, text, TPTP, TestManager, and none

C. TestManager, CQTM, TPTP, HTML, and none

D. HTML, PDF, text, TestManager, and none

Correct Answer: B

QUESTION 8

What must you do to view a comparator of a failed verification point from an RFT text log?

A. open a web browser and browse to open the file: \ \\.rftvd for the verification point you want to view

B. right-click on the test log and select Failed Verification Points from the right-click menu, then select the verification point you want to view

C. open the test log, right-click on the verification point line you want to view and select View Results from the right-click menu

D. log results in another format since you cannot open a comparator from a text log

Correct Answer: B

QUESTION 9

Which Java method advances the datapool cursor to the next row in the datapool?

A. dpMoveNext()

B. dpMoveCursor()

C. dpNext()

D. dpNextRow()

Correct Answer: C

QUESTION 10

What should the tester view to discover the current script action being executed?

A. playback monitor

B. the execution window

C. the test script

D. the application under test

Correct Answer: A