\_\_\_\_\_

**Exam** : CT0-101

Title : Convergence+ Certification

Exam

Version : DEMO

\_\_\_\_\_

1. A user is complaining that during calls the remote caller's voice intermittently cannot be heard. Which of the following is the MOST likely cause?

- A. Network to Public Switched Telephone Network (PSTN) impedance is mismatched
- B. Network packet drops on the receivers side of the conversation
- C. Network jitter is above acceptable limits on the round trip path
- D. Network packet drops on the transmitting side of the conversation

Answer: B

- 2. Which of the following BEST describes a network bottleneck?
- A. A router with multiple WAN links.
- B. A switch that is underutilized.
- C. A network with multiple switches.
- D. A router that is receiving more information than it can process.

Answer: D

- 3. Which of the following is true about jitter?
- A. Jitter is caused by insufficient network capacity.
- B. Jitter is the variation in time between the arrival of voice packets.
- C. Jitter can only be solved by using prioritization techniques.
- D. Jitter is caused by endpoints.

Answer: B

- 4. Which of the following protocols can be used in scripting call flows in an Interactive Voice Response (IVR)?
- A. HTML
- B. HTTP
- C. XML/VXML
- D. TCP/IP

Answer: C

5. Which of the following codecs would a technician configure on the VoIP server to match the voice

quality of a regular Public Switched Telephone Network (PSTN) call on a VoIP phone?

A. G. 729

B. G. 732

C. G. 722

D. G. 711

Answer: D

6. Which of the following BEST describes the functionality of a gateway? (Select TWO)

A. A device or software program that provides the central point of functionality for all VOIP calls.

B. A device or software program that provides a proxy between two systems with incompatible

technologies.

C. A device or software that navigates packets between the enterprise network and the internet.

D. A device or software that connects networks that use different protocols.

E. A device that protects against security breaches from external networks.

Answer: BD

7. A company has a contact center with thousands of distributed agents, skill-based routing, multiple hunt

groups, CTI and desktop screen pops. Management wants detailed reports about call volume and hunt

group activity within the contact center. Which of the following provides this level of detail?

A. Service Provider Multiplexer statistics

B. PBX call detail records

C. Automatic Call Distribution (ACD) reports

D. CTI server traffic reports

Answer: C

8. The voicemail system is configured to send email alerts when new voicemails are left for users. Users

are complaining they are receiving voicemails but stopped receiving email alerts. Which of the following is

the MOST likely cause of the issue?

A. Port 53 is not functioning on the email server.

\_\_\_\_\_\_

- B. Port 21 is not functioning on the voicemail server.
- C. Port 25 is not functioning on the email server.
- D. Port 63 is not functioning on the voicemail server.

Answer: C

- 9. Which of the following is the data rate of a BRI D channel?
- A. 16 Kbps
- B. 24 Kbps
- C. 32 Kbps
- D. 64 Kbps

Answer: A

- 10. All the following are correct about Unified Messaging EXCEPT:
- A. a user can setup a voice conference on demand.
- B. unified messaging is the integration of e-mail, fax and voicemail.
- C. a user can forward their voicemail in form of e-mail.
- D. a user can receive a fax in their e-mail.

Answer: A

- 11. A company is considering a telephony solution for their branch offices that is low-cost, easy to deploy and easy to manage. Which of the following is the BEST reason for the company to investigate SIP?
- A. SIP is natively meant for small deployments, yet not scalable for large deployments.
- B. SIP is natively standard, and is mature enough not to change.
- C. SIP is natively peer-to-peer, needing no infrastructure to run in simple environments.
- D. SIP is natively secure, and is not at risk of hacking or denial of service.

Answer: C

12. A technician is rolling out IP softphones in phases to telecommuters. During the pilot and initial production deployment, no problems were noted. But after a major increase in the number of remote users, all callers begin to complain of voice quality issues, while main site users experience no issues. Which of the following should the technician investigate? (Select TWO)

Instant Download	PDF And VCE	100% Passing Guarantee	100% Money Back Guarantee
A. Network Address Tr	anslation (NAT) co	nfigurations	
B. Firewall port and CF	<sup>2</sup> U utilization		
C. IP PBX port and CP	'U utilization		
D. Bandwidth utilization	n on Internet circuit	t	
E. Softphone QoS sett	ings		
Answer: BD			
13. Which of the follow	ing devices has to	be connected to every user of a	an H. 323 conference?
A. Media Gateway Cor	ntroller		
B. Gatekeeper			
C. Terminal			
D. Multipoint Control U	Init (MCU)		
Answer: D			
		.XJ	
14. Which of the follow	wing network topo	logies would make it possible	for a remote site to continue to
communicate during a	complete main site	e outage?	
A. Frame Relay netwo	rk		
B. Stub network		9	
C. Hub and Spoke net	work		
D. Meshed network Ar	nswer:		
D	*		
15. Identify the compo	nents needed for a	softphone end-point: (Select TI	HREE)
A. PC			
B. USB drive			
C. Analog phone			
D. Microphone			
E. Sound card			
F. Network cable			

Answer: ADE

5

16. A technician is responsible for sending a training video to a potential client for review, the technician must identify this videos ownership without impairing the functionality to the viewers. Which of the following forms of data security is this referred to as?

- A. Root Kit
- B. Public Key Encryption
- C. Content Scramble System (CSS)
- D. Watermarking

Answer: D

- 17. An IP softphone user is complaining of an echo on external calls. Which of the following is MOST likely the cause?
- A. Headset speaker is too close to the microphone.
- B. Routers are introducing feedback.
- C. Sidetones are not being filtered.
- D. The soundcard volume is set too low.

Answer: A

- 18. Which of the following is necessary in order to have internet connectivity to multiple Internet Service Providers (ISP)?
- A. BGP-4
- B. RIP C.

IS-IS D.

**OSPF** 

Answer: A

- 19. The mapping of internet service addresses to E. 164 numbering is addressed by:
- A. ENUM.
- B. SNMP.
- C. CDR.

\_\_\_\_\_

D. SS7.

Answer: A

- 20. Which are the following are the reasons why the wire pairs in CAT5 cables are twisted? (Select TWO).
- A. Twisting eliminates electric interference from adjacent wires.
- B. Twisting distributes electric interference evenly to both wires.
- C. Twisting provides additional tensile strength to the cable.
- D. Twisting eliminates cross-talk between adjacent pairs.
- E. Twisting minimizes the contact area of adjacent wires to sources of interference.

Answer: BE

## **Trying our product!**

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

## **Need Help**

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:





## Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.