E20-361 ^{Q&As}

Network Attached Storage (NAS) Implementation Exam

Pass EMC E20-361 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/e20-361.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

365 Days Free Update

800,000+ Satisfied Customers

QUESTION 1

Due to a Control Station failure, a customer is now concerned about the availability of their Data Mover in case of a Data Mover failover. What would you tell the customer?

A. Control Station needs to be running for a Data Mover failover to occur

B. Data Mover failover does not depend on the Control Station to occur

C. Data Mover failover will occur but failback will fail

D. Data Mover will lose all the connections

Correct Answer: A

QUESTION 2

Which forms of Windows domain authentication are supported by Celerra?

A. ACF2 and Kerberos

B. Internet Key Exchange and NTLM

C. NTLM and Kerberos

D. NTLM and Microsoft Point-to-Point Encryption

Correct Answer: C

QUESTION 3

In an iSCSI architecture model, what is the default TCP port?

A. 3260

B. 3268

C. 8260

D. 8888

Correct Answer: A

QUESTION 4

When creating a file system using Celerra Manager, which kind of licensing must be in place to permit the use of the Automatic Volume Manager?

A. Advanced Edition

B. Enhanced Edition

C. Extended Edition

D. No licensing is necessary

Correct Answer: D

QUESTION 5

A site administrator would like to have file system quota implemented. However, the administrator is worried about users who create symbolic links.

How can symbolic links be excluded from the file system quota?

A. Use the filesize policy

B. Use the block policy

C. Use group and user quotas together

D. Use the excl option when configuring the quota

Correct Answer: A

QUESTION 6

In a backup environment, which username and password is configured on the Ceierra for backup operations?

A. Celerra administrator

B. Domain administrator

C. ISV software account

D. NDMP account

Correct Answer: D

QUESTION 7

A Celerra administrator is implementing a native iSCSI solution. The following steps were executed in order to implement the solution:

-

Created the iSCSI targets

-

Created and mounted a file system dedicated to iSCSI storage

-

Created the iSCSI LUNs and the LUN masks

However, the administrator is unable to log in to the targets. What is the cause of the problem?

A. iSCSI service is stopped.

B. iSNS server is misconfigured.

C. Initiator is unregistered.

D. CHAP authentication is disabled.

Correct Answer: A

QUESTION 8

What is one property of the default CIFS server?

A. Can be used to access all shares on the Data Mover

B. Has a hidden CIFS name of DEFAULT

C. Uses all assigned IP interfaces on the Data Mover

D. Uses all unassigned IP interfaces on the Data Mover

Correct Answer: D

QUESTION 9

Which zoning method allows the storage administrator to replace an HBA. without changing the associated zoning?

A. Host

B. Port

C. Server

D. WWN

Correct Answer: B

QUESTION 10

File systems created for iSCSI LUNs should be large enough to accommodate which objects?

A. iSCSI LUNs and snaps

B. iSCSI LUNs

C. iSCSI LUNs and CIFS

D. iSCSI LUNs and NFS

Correct Answer: A

QUESTION 11

In a Celerra environment, where does the Celerra Antivirus Agent run?

A. Control Station

B. Data Mover

C. Data Mover and Control Station

D. Windows Server

Correct Answer: D

QUESTION 12

What is limited to 15 characters?

A. DOS filename

B. Forward lookup zone

C. Hostname

D. NetBIOS name

Correct Answer: D

QUESTION 13

What must be done in for the CIFS server to appear in Active Directory?

A. Add server to DNS

B. Add to domain using DFS

C. Join CIFS server to domain

D. Manually start the CIFS server

Correct Answer: C

QUESTION 14

What address ranges do the two Celerra internal networks use?

A. 128.221.253.0 network with netmask 255.255.255.0 and 128.221.252.0 network with netmask 255.255.255.0

B. 128.221.0.0 network with netmask 255.255.0.0 and 128.222.0.0 network with netmask 255.255.0.0

C. 128.221.1.248 network with netmask 255.255.255.248 and 128.221.1.240 network with netmask 255.255.255.248

D. 192.168.1.0 network with netmask 255.255.255.0 and 192.168.2.0 network with netmask 255.255.255.248

Correct Answer: A

QUESTION 15

What is an environmental requirement for a simplified install on a single Data Mover NS system with a fabric-attached CLARiiON back-end?

A. A parallel connection between the Data Mover and the Control Station

B. At least one uncommitted zone

C. Ensure four unused SP ports are available

D. Ensure two unused SP ports are available

Correct Answer: D

Latest E20-361 Dumps   E20-361 Study Guide   E20-361 Braindumps