



HC-611^{Q&As}

Huawei Certified Network Associate - Building the Structure of Storage Network (HCNA-BSSN)

Pass Huawei HC-611 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hc-611.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

SAN storage devices on the power flow to the right:

- A. Control Box - HDD Box - Switch - server
- B. HDD Box - Control box - switch - server
- C. Server - switch - Control Box - Hard Box
- D. Server - Switch - Hard box - Control Box

Correct Answer: B

QUESTION 2

A switching fabric switch port is connected to a fiber optic hub port, then see from this port fiber switch type yes.

- A. G-Port
- B. E-Port
- C. F-Port
- D. FL-Port

Correct Answer: D

QUESTION 3

About the S2600 storage array supports hard statement is correct?.

- A. The same control box support intermixing SAS and SATA disk
- B. Control box safe dish disk support mixed interpolation
- C. Unified control box support intermixing SAS and FC drives
- D. If you want to create a RAID group,RAID disk support group under the same mixed interpolation

Correct Answer: A

QUESTION 4

In the same RAID group, allowing simultaneous failure of two members of the panel and still full RAID -level data may have () (Choose three)

- A. RAID1



- B. RAID 6
- C. RAID 5
- D. RAID01

Correct Answer: ABD

QUESTION 5

Linux system, the MBR disk to GPT format to use what commands:

- A. parted
- B. fdisk
- C. diskpart
- D. mount

Correct Answer: A

QUESTION 6

With a new PC, when you first use the ISM manage storage devices when you connect the network cable management in the IE address bar enter: <http://192.168.128.101>, will pop up an ISM management interface, then What operating normally need to install the software? (Choose two)

- A. ISM management software installed on the PC client to
- B. Install the JRE software
- C. Multipathing software installation
- D. Install iSCSI initiator

Correct Answer: AB

QUESTION 7

If the S2600's A controller management port IP address is 192.168.128.101, IP address B controller manages the port 192.168.128.102, the array controller has two iscsi each host port, if A controlled 00 iscsi host port is 192.168.10.101, 01iscsi host port A control is 192.168.11.101, then B iscsi host port control 01 which of the following segments can (assuming the mask is 24) (Choose three)

- A. 192.168.128.0
- B. 192.168.10.0
- C. 192.168.11.0



D. 192.168.12.0

Correct Answer: BCD

QUESTION 8

SAN storage systems, real-time monitoring disk status, the suspected faulty disk data migration to hot spare disk is called:

- A. Reconstruction
- B. Reconstruction
- C. Disk pre-copy
- D. Disk Sleep

Correct Answer: C

QUESTION 9

Using TCP / IP network protocol bearer FC channel are: (Choose three)

- A. iFCP
- B. IPFC
- C. FCIP
- D. FCoE

Correct Answer: ACD

QUESTION 10

About switched fabric network topology, which of the following is correct? (Choose three)

- A. The number of devices that can connect up to approximately 16 million
- B. Device to establish a network connection is permanent
- C. While a plurality of connection establishment
- D. Each device shared bandwidth

Correct Answer: ABC

QUESTION 11



The basic starting point is to use proven iSCSI IP network and data transmission technology to achieve extended SAN systems.

A. True

B. False

Correct Answer: A

QUESTION 12

Port on S2600 and back-end disk storage control box is connected to the frame (), which is 12Gb SAS wide ports.

A. FC

B. SAS EXP

C. SAS PRI

D. iSCSI

Correct Answer: B

QUESTION 13

ISM configuration interface support through a wizard to configure the host.

A. True

B. False

Correct Answer: A

QUESTION 14

FC configuration when connected to the host and the array, host software must be installed and configured initiator.

A. True

B. False

Correct Answer: B

QUESTION 15

In S5000T, for example, the principle of fault diagnosis for storage devices: (Choose three)



- A. First diagnosis of external factors,internal factors after diagnosis.
- B. First diagnosis overall,partial diagnosis.
- C. First analysis of high-level alarm,low level alarm after analysis.
- D. First check service after checking storage

Correct Answer: ABC

[HC-611 PDF Dumps](#)

[HC-611 Practice Test](#)

[HC-611 Braindumps](#)