



HCE-5710^{Q&As}

Architecting Hitachi Data Systems Certified Expert - Replication solutions

Pass Hitachi HCE-5710 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/hce-5710.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

One CCI instance fails to start. You decide to review the HORCM logs to determine what is wrong. Where are the logs stored?

- A. Under /var/adm.
- B. On the Command Device.
- C. Always under Horcm/log/curlog.
- D. It depends on the environment variable.

Correct Answer: D

QUESTION 2

The Command Control Interface (CCI) for the Universal Replicator pair operation displays a PFUS split type. Which three statements are true? (Choose three.)

- A. The PFUL status is displayed as PAIR status by Storage Navigator.
- B. The PFUS status is displayed as PSUS status by Storage Navigator.
- C. The pair status will change from PFUS to PSUE when the primary Journal Group is full.
- D. The pair status changes from PFUL to PFUS when the primary Journal Group is 80 percent full.
- E. The pair status will change from PFUL to PFUS when the "data overflow watch" time period is exceeded.

Correct Answer: ABE

QUESTION 3

An Hitachi Data Systems customer is implementing a TrueCopy solution on a Universal Storage Platform (USP). Where would you obtain the latest information regarding supported features and hardware?

- A. Country Product Manager
- B. USP User and Reference Guide
- C. USP TrueCopy User and Reference Guide
- D. Microcode ECN (Engineering Change Notice)

Correct Answer: A

QUESTION 4



A customer has a multi-target Three Data Center (3DC) implementation to protect a mission critical UNIX application. The production host crashes, but the array and network are still working. The customer wants to bring up the application on a host at the local data center and still maintain two remote copies of the data, What must be performed first at the local data center?

- A. Perform swap takeover for the HUR pairs.
- B. Perform swap takeover for the TrueCopy pairs.
- C. Perform Delta Resync between the local and remote arrays.
- D. Perform Delta Resync between the local and production arrays.

Correct Answer: B

QUESTION 5

What are three key points a customer must consider when establishing a Three Data Center (3DC) Business Continuity Solution)? (Choose three.)

- A. The customer must decide which type of 3DC to install.
- B. The customer must decide the size of the metadata area on each journal volume.
- C. The customer must decide the ratio of metadata to real data on each journal volume.
- D. The customer must decide the link type and performance between the local and distant USP.
- E. The customer must decide the type and number of Parity Groups necessary to obtain the size and performance of the Journal Groups.

Correct Answer: ADE

QUESTION 6

If a customer has a server cluster, what does a quorum disk do? (Choose two.)

- A. It is a configuration database.
- B. It tells the applications what storage to access.
- C. It decides where to run an application if a node fails.
- D. It tells the storage which applications are accessing it.

Correct Answer: AC

QUESTION 7



The Hitachi HiCommand Protection Manager (HPtM) software uses Volume Shadow Copy Service (VSS) to protect mission critical databases, file systems and application data, Which three components does VSS coordinate to achieve this? (Choose three.)

- A. The application that requests VSS services.
- B. The programs that manage shadow copies.
- C. Copy-on-Write SnapShot designed for VSS.
- D. Hitachi Software that allows you to present storage.
- E. Applications that store persistent information on disk.

Correct Answer: ABE

QUESTION 8

A customer wishes to copy a database on external storage controlled by a Universal Storage Platform over 10km using TrueCopy Synchronous. Which HiCommand product is used to manage the replication?

- A. HiCommand Device Manager (HDvM)
- B. HiCommand Protection Manager (HPtM)
- C. HiCommand Replication Monitor (HRpM)
- D. HiCommand Tiered Storage Manager (HTsM)

Correct Answer: A

QUESTION 9

A customer has a Windows CCI server controlling both Universal Replicator and ShadowImage pairs. The customer would like to see the status of the Universal Replicator pairs. Which command can the customer issue prior to using the pairdisplay command to ensure only the status of the Universal Replicator pairs are shown?

- A. set HORCC_MRCF=
- B. unset HORCC_MRCF
- C. set HORCC_MRCF=1
- D. export HORCC_MRCF=1

Correct Answer: A

QUESTION 10



Which two statements describe HiCommand Tiered Storage Manager? (Choose two.)

- A. Tiered Storage Manager can migrate data within subsystems.
- B. Tiered Storage Manager can migrate data between external subsystems.
- C. Tiered Storage Manager can migrate data only between external subsystems.
- D. Tiered Storage Manager can migrate data only between a subsystem and an external subsystem.

Correct Answer: AB

QUESTION 11

A customer has a number of applications on different operating systems. These applications require fail-over capability. The customer has chosen the appropriate cluster technology for each platform. With which two cluster types is Hitachi Data Systems allowed to integrate? (Choose two.)

- A. Sun Cluster
- B. MetroCluster
- C. Veritas Cluster
- D. Continental Cluster

Correct Answer: AC

QUESTION 12

A customer has a cascaded Three Data Center (3DC) implementation to protect a mission critical UNIX application. The production host crashes, but the array and network are still up. The customer wants to bring up the application on a host at the local data center and still maintain two remote copies of the data; What must be performed first at the local data center?

- A. Suspend HUR pairs.
- B. Suspend TrueCopy pairs.
- C. Perform swap takeover for the HUR pairs.
- D. Perform swap takeover for the TrueCopy pairs.

Correct Answer: A

QUESTION 13

A customer is considering using TrueCopy to a site 10km distant for an application that has high write content with fairly severe SLAs. Which two must be considered? (Choose two.)

- A. Consistency Groups must be used.



- B. A link with minimum latency must be used.
- C. A link with maximum bandwidth must be used.
- D. The database buffers must be flushed frequently to ensure consistency.

Correct Answer: BC

QUESTION 14

A ShadowImage CCI environment has been scripted so that the pairs resynchronize and suspend each hour using the latest version of CCI. ShadowImage has been configured to use consistency groups and At-Time Split. The ShadowImage CCI device group name is SI_db01. Which CCI command should be included in the script following the pairresync command to allow time for the ShadowImage pairs to be fully resynchronized?

- A. pairvolchk -g SI_db01 -c -ss -nomsg
- B. pairvolchk -g SI_db01 -c -ss -t 3600
- C. pairevwait -g SI_db01 -s pair -nowait
- D. pairevwait -g SI_db01 -ss pair -t 3600

Correct Answer: D

QUESTION 15

On the Storage Navigator frame for a TrueCopy pair operation, the "Status" column indicates PDUB. What is the status of the pairs indicating PDUB?

- A. This is a TrueCopy LUSE status of a pair suspended error.
- B. This status indicates that the TrueCopy pair is in the initial copy.
- C. One or more LDEV pairs are SMPL on a TrueCopy LUSE volume.
- D. The status of the TrueCopy software LUSE volume is in the initial copy.

Correct Answer: C

[HCE-5710 VCE Dumps](#)

[HCE-5710 Study Guide](#)

[HCE-5710 Brindumps](#)