

HH0-220^{Q&As}

HDS Certified Implmenter-Modular

Pass Hitachi HH0-220 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/hh0-220.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Which two statements accurately describe the Program Product functions available on Hitachi Unified Storage (HUS) systems? (Choose two.)

- A. LUN resizing is a basic function in SNM2 and does not require a separate license key.
- B. The Tray Power Saving function does require a separate license key.
- C. Restricting access to a HUS Command Device is possible using Account Authentication.
- D. Hitachi Dynamic Link Manager is used to control the HUS active/active controller feature.

Correct Answer: AB

QUESTION 2

A manufacturing company wants to centrally manage all their multipath software using Hitachi Global Link Manager (HGLM). Which two types of multipath software are supported? (Choose two.)

- A. HDLM
- B. VxDMP
- C. PowerPath
- D. SDD
- Correct Answer: AB

QUESTION 3

A customer wants to migrate their data from an existing AMS2500 to a newly acquired Hitachi Unified Storage (HUS) system using TrueCopy Extended Distance (TCE) software. Which set of components is required on the HUS to configure TCE?

- A. Journal Volumes and a TCE license
- B. an HDP license and 50% more cache capacity
- C. an HDP License and a TCE license
- D. a Cache Memory adapter and a TCE license

Correct Answer: C

QUESTION 4

What allows firmware to be updated non-disruptively on the Hitachi Unified Storage systems?

- A. Firmware updates are performed in less than the host I/O timeout value.
- B. While one controller is rebooting, the other handles all host operations.
- C. Host connectivity to both controllers established using multi-pathing software.
- D. Firmware updates only affect the first five drives and no controller reboot is required.

Correct Answer: B

QUESTION 5

What are three characteristics of the Hitachi Unified Storage systems active/active controller design? (Choose three.)

- A. SNM2 GUI is used to turn on active/active controller processing.
- B. Workload is automatically balanced between controllers.
- C. When creating a LUN the default controller must be selected.
- D. The processor of CtIr0 can access the Fibre Channel (FC) ports of Ctrl1.
- E. Non disruptive firmware upgrade is possible even if a host is connected by only one path.

Correct Answer: BDE

QUESTION 6

Which two statements relating to the online firmware upgrade are true for Hitachi Unified Storage systems? (Choose two.)

- A. Only the HUS model 150 storage system supports online firmware upgrades.
- B. Online firmware upgrades should not be scheduled for periods of high CPU workload.
- C. Online firmware upgrades can only be done using Storage Navigator Modular 2.
- D. All hosts must have multiple paths to the HUS when performing online firmware upgrades.

Correct Answer: BC

QUESTION 7

Yesterday you allocated five new LUNs for a Solaris 9 host. Today the Solaris administrator is concerned about corrupt data because the host system log has several entries referencing the new LUNs with the following message: "Corrupt label; wrong magic number". What do you tell the Solaris administrator?

- A. That they need to configure Device Mapper for the newly allocated LUNs.
- B. That they should shut down the server right away and that you will allocate five new LUNs.



C. That the message is normal for new LUN allocations and that they just need to label the new partitions.

D. That the Master Boot Record (MBR) on one of the disks has become corrupt and that rebooting the host should fix the issue.

Correct Answer: C

QUESTION 8

When performing an initial installation of a Hitachi Unified Storage system, which management tool must be used to set the date and time?

A. Web Tool

- B. RAID Manager/CCI
- C. Hitachi Command Suite
- D. Storage Navigator Modular 2

Correct Answer: D

QUESTION 9

A customer wants to configure a specific 5GB LUN for the fastest possible response time on a Hitachi Unified Storage system. Which feature should be used?

- A. Cache Partition Manager
- **B.** Volume Migration
- C. Cache Residency Manager
- D. Data Retention Utility

Correct Answer: C

QUESTION 10

What is the purpose of the System Assurance documentation?

- A. to ensure accurate and complete record of pre-installation data
- B. to guarantee that Hitachi Data Systems equipment is insured during transportation
- C. to inform a channel partner that equipment is available for shipment
- D. to validate configuration changes for customers with a premium service contract

Correct Answer: A



QUESTION 11

Which method is used by Hitachi Unified Storage (HUS) systems to protect against loss of data in cache should a total power failure occur?

- A. The battery power de-stages data in cache to an on-board SSD drive.
- B. The HUS uses non-volatile cache so data is always protected.
- C. The battery power de-stages data in cache to on-board Flash memory.
- D. The HUS mirrors all cache writes to on-board SSD drives.

Correct Answer: C

QUESTION 12

What are two ways to register a new Hitachi Unified Storage system with Storage Navigator Modular 2? (Choose two.)

- A. SNM2 can scan a range of IP addresses.
- B. SNM2 can import a .CSV file containing IP addresses.
- C. The controller IP addresses can be entered into SNM2.
- D. SNM2 automatically detects connected arrays using UDP broadcasts.

Correct Answer: AC

QUESTION 13

Which two apply when replacing a disk on a Hitachi Unified Storage (HUS) system? (Choose two.)

- A. A wrist strap must be used when replacing disk drives.
- B. The faulty drive must be blocked using SNM2 before replacement
- C. The HUS needs to be in maintenance mode when disks are replaced.
- D. The Web tool should be used to confirm that the replacement is successful.

Correct Answer: A

QUESTION 14

You want to add an account for a new storage administrator on a Hitachi Unified Storage system using Storage Navigator Modular 2. Which Account Authentication role must you have to be able to perform this task?

A. Storage Administrator (View and Modify)



- B. Account Administrator (View and Modify)
- C. Security Administrator (View and Modify)
- D. Authentication Administrator (View and Modify)

Correct Answer: B

QUESTION 15

Which two Program Products reserve cache in a Hitachi Unified Storage system when they are installed, even if disabled? (Choose two.)

A. TrueCopy

- B. Cache Partioning Manager
- C. ShadowImage
- D. TrueCopy Extended

Correct Answer: BD

HH0-220 PDF Dumps

HH0-220 VCE Dumps

HH0-220 Study Guide