
Exam : HP0-662

Title : NonStop Configuration and

Planning

Version : DEMO

1. Assuming no I/O enclosures, how many electrical branch circuits are needed to provide power fault tolerance for a six-processor S7x000 system? A. 2 B. 3 C. 4 D. 6 Answer: D 2. Which items would you expect to see on a network topology diagram? Select TWO. A. tape devices B. IP addresses C. routers D. disk mapping E. cable specifications Answer: BC 3. What allows a customer to track open problem cases through the Web? A. Scout for NonStop servers B. Express Notice C. NonStop Technical Library (NTL) D. Total Web Support (TWS) Answer: D 4. Which prediction is NOT produced by TCM? A. number of processors required B. number of logical disk volumes C. network response time D. processor and disk utilization

5. Which tool simplifies the task of migrating a database from many small disks to a smaller number of

Answer: C

large disks?
A. MEDIACOM
B. ASAP
C. SMF
D. MAPPER
Answer: C
6. DSM/SCM can be used to control customer software. Which program is used to prepare the
software?
A. CNFGINFO
B. ZPHIRNM C.
INITENV
D. INITSTAT
Answer: A
7. To what type of adapter does a default configuration system console connect?
A. E4SA
B. MIOE
C. FESA
D. TRSA
Answer: B
8. Which process needs to be configured to ensure Expand connectivity between two systems?
A. \$znet
B. \$ncp
C. \$expand
D. \$zzatm
Answer: B
9. How many internal disk SCSI controllers are on a PMF CRU?

A. 0
B. 1
C. 2
D. 3
Answer: C
10. Which element is typically included in a separate document in response to a Request for Proposal
(RFP)?
A. software details
B. timescales
C. cost breakdown
D. hardware details
Answer: C
11. Increasing the number of processors in a system
A. provides fault tolerance for the system consoles
B. allows more disk units in group 1 of the system
C. requires a cold load of the system
D. allows more low-pin processes to run in the system
Answer: D
12. Which product can be used to project transaction growths into a resource upgrade timeline?
A. GPA
B. ASAP
C. NSX
D. TCM
Answer: D
13. What is the filename of the SCSI boot code for the G06.08 release?
A. I1000

· ·	
	•
B. IBOOT	
C. I2000	
D. ISCSI	
Answer: B	
14. Which utility is used for routine tape management operations?	
A. TAPECOM	
B. NSKCOM	
C. MEDIACOM	
D. TMFCOM	
Answer: C	
15. Which product requires a manual firmware update using TSM?	
A. FESA	
B. E4SA C.	
SWAN D.	
TRSA	
Answer: C	
16. Which tool has replaced Timbuktu for remote support?	
A. Timbuk3	
B. Remote Copy	
C. Carbon Copy	
D. PC Anywhere	
Answer: C	
17. What is a key difference between TSM low-level link and TSM service connection?	
A. service connection communicates only with the MSP	
B. service connection shows external devices	

C. service connection allows firmware updates

D. service connection allows system discovery

Answer: B

- 18. Which Windows NT services are required when configuring dial-out on TSM? Select TWO.
- A. RPC
- B. RAS
- C. SAP Agent
- D. Network Monitor Agent
- E. SNMP

Answer: BE

- 19. In which volume and subvolume do the hardware configuration files reside?
- A. \$system.system
- B. \$system.sysnn
- C. \$system.zsysconf
- D. \$dsmscm.system

Answer: C

- 20. How can the ServerNet connectivity to CPU 5 be displayed in SCF?
- A. INFO SERVERNET 5
- **B. STATUS SERVERNET \$ZSNET**
- C. INFO SERVERNET \$ZSNET
- D. STATUS SERVERNET 5

Answer: B

Trying our product!

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:





Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.