



# NSE7\_EFW<sup>Q&As</sup>

NSE7 Enterprise Firewall - FortiOS 5.4

**Pass Fortinet NSE7\_EFW Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

[https://www.pass4itsure.com/nse7\\_efw.html](https://www.pass4itsure.com/nse7_efw.html)

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

View the exhibit, which contains the output of a web diagnose command, and then answer the question below.

```
# diagnose webfilter fortiguard statistics list

Rating Statistics:
-----
DNS failures          : 273
DNS lookups           : 280
Data send failures   : 0
Data read failures   : 0
Wrong package type   : 0
Hash table miss      : 0
Unknown server       : 0
Incorrect CRC         : 0
Proxy requests failures : 0
Request timeout      : 1
Total requests       : 2409
Requests to FortiGuard servers : 1182
Server errored responses : 0
Relayed rating       : 0
Invalid profile      : 0

Allowed              : 1021
Blocked              : 3909
Logged               : 3927
Blocked Errors       : 565
Allowed Errors       : 0
Monitors             : 0
Authenticates        : 0
Warnings             : 18
Ovrd request timeout : 0
Ovrd send failures   : 0
Ovrd read failures   : 0
Ovrd errored responses : 0
...

# diagnose webfilter fortiguard statistics list

Cache Statistics:
-----
Maximum memory      : 0
Memory usage        : 0

Nodes               : 0
Leaves              : 0
Prefix nodes        : 0
Exact nodes         : 0

Requests            : 0
Misses              : 0
Hits                : 0
Prefix hits         : 0
Exact hits          : 0

No cache directive  : 0
Add after prefix    : 0
Invalid DB put      : 0
DB updates          : 0

Percent full        : 0%
Branches            : 0%
Leaves              : 0%
Prefix nodes        : 0%
Exact nodes         : 0%

Miss rate           : 0%
Hit rate            : 0%
Prefix hits         : 0%
Exact hits          : 0%
```

Which one of the following statements explains why the cache statistics are all zeros?

- A. The administrator has reallocated the cache memory to a separate process.
- B. There are no users making web requests.
- C. The FortiGuard web filter cache is disabled in the FortiGate's configuration.
- D. FortiGate is using a flow-based web filter and the cache applies only to proxy-based inspection.

Correct Answer: D

### QUESTION 2

View the exhibit, which contains a session entry, and then answer the question below.



```
session info: proto=1 proto_state=00 duration=1 expire=59 timeout=0 flags=00000000
sockflag=00000000 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=log may_dirty none
statistic(bytes/packets/allow_err): org=168/2/1 reply=168/2/1 tuples=2
tx speed(Bps/kbps): 97/0 rx speed(Bps/kbps): 97/0
orgin->sink: org pre->post, reply pre->post dev=9->3/3->9 gwy=10.200.1.254/10.1.0.1
hook=post dir=org act=snat 10.1.10.10:40602->10.200.5.1:8(10.200.1.254/10.1.0.1
hook=pre dir=reply act=dnat 10.200.5.1:60430->10.200.1.1:0(10.1.10.10:40602)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=0002a5c9 tos=ff/ff app_list=0 app=0 url_cat=0
dd_type=0 dd_mode=0
```

Which statement is correct regarding this session?

- A. It is an ICMP session from 10.1.10.10 to 10.200.1.1.
- B. It is an ICMP session from 10.1.10.10 to 10.200.5.1.
- C. It is a TCP session in ESTABLISHED state from 10.1.10.10 to 10.200.5.1.
- D. It is a TCP session in CLOSE\_WAIT state from 10.1.10.10 to 10.200.1.1.

Correct Answer: A

### QUESTION 3

View the exhibit, which contains the partial output of a diagnose command, and then answer the question below.

```
Spoke-2 # dia vpn tunnel list
list all ipsec tunnel in vd 0
name=VPN ver=1 serial=1 10.200.5.1:0->10.200.4.1:0
bound_if=3 lgwy=static/1 tun=intf/0 mode=auto/1 encaps=none/0
proxyid_num=1 child_num=0 refcnt=15 ilast=10 olast=792 auto-discovery=0
stat: rxp=0 txp=0 rxb=0 teb=0
dpd: mode=on-demand on=1 idle=20000 ms retry=3 count=0 seqno=0
natt: mode=none draft=0 interval=0 remote_port=0
proxyid=VPN proto=0 sa=1 ref=2 serial=1
  src: 0:10.1.2.0/255.255.0:0
  dst: 0:10.1.1.0/255.255.255.0:0
  SA: ref=3 options=2e type=00 soft=0 mtu=1438 expire=42403/0B replaywin=2048 segno=1 esn=0
replaywin_lastseq=000000000
life: type=01 bytes=0/0 timeout=43177/43200
dec: spi=ccclf66d esp=aes key=16 280e5cd6f9bacc65ac771556c464ffbd
  ah=shal key=20 c68091d68753578785de6a7a6b276b506c527efe
enc: spi=df14200b esp=aes key=16 b02a7e9f5542b69aff6aa391738ee393
  ah=shal key20 889f7529887c215c25950be2ba86e6fela5367be
dec: pkts/bytes=0/0, enc:pkts/bytes=0/0
```



Based on the output, which of the following statements is correct?

- A. Anti-reply is enabled.
- B. DPD is disabled.
- C. Quick mode selectors are disabled.
- D. Remote gateway IP is 10.200.5.1.

Correct Answer: A

---

#### QUESTION 4

View the exhibit, which contains a partial output of an IKE real-time debug, and then answer the question below.

Based on the debug output, which phase-1 setting is enabled in the configuration of this VPN?

- A. auto-discovery-sender
- B. auto-discovery-forwarder
- C. auto-discovery-shortcut
- D. auto-discovery-receiver

Correct Answer: C

---

#### QUESTION 5

Two independent FortiGate HA clusters are connected to the same broadcast domain. The administrator has reported that both clusters are using the same HA virtual MAC address. This creates a duplicated MAC address problem in the network.

What HA setting must be changed in one of the HA clusters to fix the problem?

- A. Group ID.
- B. Group name.
- C. Session pickup.
- D. Gratuitous ARPs.

Correct Answer: A

---

#### QUESTION 6





View the exhibit, which contains an entry in the session table, and then answer the question below.

```
session info: proto=6 proto_state=11 duration=53 expire=265 timeout=300 flags=00000000
sockflag=00000000
origin-shaper=
reply-shaper=
per_ip_shaper=
ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
user=AALI state=redir log local may_dirty npu nlb none acct-ext
statistic (bytes/packets/allow_err): org=2651/17/1 reply=19130/28/1 tuples=3
tx speed (Bps/kbps): 75/0 rx speed (Bps/kbps): 542/4
orgin->sink: org pre->post, reply pre->post dev=7->6/6->7 gwy=172.20.121.2/10.0.0.2
hook=post dir=org act=snat 192.167.1.100:49545->216.58.216.238:443 (172.20.121.96:49545)
hook=pre dir=reply act=dnat 216.58.216.238:443->172.20.121.96:49545 (192.167.1.100:49545)
hook=post dir=reply act=noop 216.58.216.238:443->192.167.1.100:49545 (0.0.0.0:0)
pos/(before, after) 0/(0,0), 0/(0,0)
src_mac=08:5b:0e:6c:7b:7a
misc=0 policy_id=21 auth_info=0 chk_client_info=0 vd=0
serial=007f2948 tos=ff/ff app_list=0 app=0 url_cat=41
dd_type=0 dd_mode=0
npu_state=00000000
npu info: flag=0x00/0x00, offload=0/0, ips_offload=0/0, epid=0/0, ipid=0/0, vlan=0x0000/0x0000
vlifid=0/0, vtag_in=0x0000/0x0000 in_npu=0/0, out_npu=0/0, fwd_en=0/0, qid=0/0
```

Which one of the following statements is true regarding FortiGate's inspection of this session?

- A. FortiGate applied proxy-based inspection.
- B. FortiGate forwarded this session without any inspection.
- C. FortiGate applied flow-based inspection.
- D. FortiGate applied explicit proxy-based inspection.

Correct Answer: B

## QUESTION 7

Examine the output of the `get router info bgp summary` command shown in the exhibit; then answer the question below.



```
# get router info bgp summary
BGP router identifier 0.0.0.117, local AS number 65117
BGP table version is 104
3 BGP AS-PATH entries
0 BGP community entries
```

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.125.0.60	4	65060	1698	1756	103	0	0	03:02:49	1
10.127.0.75	4	65075	2206	2250	102	0	0	02:45:55	1
10.200.3.1	4	65501	101	115	0	0	0	never	Active

Which statements are true regarding the output in the exhibit? (Choose two.)

- A. BGP state of the peer 10.125.0.60 is Established.
- B. BGP peer 10.200.3.1 has never been down since the BGP counters were cleared.
- C. Local BGP peer has not received an OpenConfirm from 10.200.3.1.
- D. The local BGP peer has received a total of 3 BGP prefixes.

Correct Answer: AC

### QUESTION 8

View the exhibit, which contains the output of a BGP debug command, and then answer the question below.

```
# get router info bgp summary
BGP router identifier 0.0.0.117, local AS number 65117
BGP table version is 104
3 BGP AS-PATH entries
0 BGP community entries
```

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.125.0.60	4	65060	1698	1756	103	0	0	03:02:49	1
10.127.0.75	4	65075	2206	2250	102	0	0	02:45:55	1
10.200.3.1	4	65501	101	115	0	0	0	never	Active

Total number of neighbors 3

Which of the following statements about the exhibit are true? (Choose two.)

- A. For the peer 10.125.0.60, the BGP state of is Established.
- B. The local BGP peer has received a total of three BGP prefixes.
- C. Since the BGP counters were last reset, the BGP peer 10.200.3.1 has never been down.



D. The local BGP peer has not established a TCP session to the BGP peer 10.200.3.1.

Correct Answer: BC

### QUESTION 9

An administrator has decreased all the TCP session timers to optimize the FortiGate memory usage. However, after the changes, one network application started to have problems. During the troubleshooting, the administrator noticed that the FortiGate deletes the sessions after the clients send the SYN packets, and before the arrival of the SYN/ACKs. When the SYN/ACK packets arrive to the FortiGate, the unit has already deleted the respective sessions. Which TCP session timer must be increased to fix this problem?

- A. TCP half open.
- B. TCP half close.
- C. TCP time wait.
- D. TCP session time to live.

Correct Answer: A

### QUESTION 10

View these partial outputs from two routing debug commands:

```
# get router info kernel
tab=254 vf=0 scope=0 type=1 proto=11 prio=0 0.0.0.0/0.0.0.0/0->0.0.0.0/0 pref=0.0.0.0 gwy=10.200.1.254
dev=2(port1)
tab=254 vf=0 scope=0 type=1 proto=11 prio=0 0.0.0.0/0.0.0.0/0->0.0.0.0/0 pref=0.0.0.0 gwy=10.200.2.254
dev=3(port2)
tab=254 vf=0 scope=253 type=1 proto=2 prio=0 0.0.0.0/0.0.0.0/0->10.0.1.0/24 pref=10.0.1.254 gwy=0.0.0.0
dev=4(port3)
# get router info routing-table all
s* 0.0.0.0/0 [10/0] via 10.200.1.254, port1
   [10/0] via 10.200.2.254, port2, [10/0]
c 10.0.1.0/24 is directly connected, port3
c 10.200.1.0/24 is directly connected, port1
c 10.200.2.0/24 is directly connected, port2
```

Which outbound interface will FortiGate use to route web traffic from internal users to the Internet?

- A. Both port1 and port2
- B. port3
- C. port1
- D. port2

Correct Answer: C

**QUESTION 11**

Examine the output of the `diagnose ips anomaly list` command shown in the exhibit; then answer the question below.

```
# diagnose ips anomaly list
```

```
list nids meter:
```

id=ip_dst_session	ip=192.168.1.10	dos_id=2	exp=3646	pps=0	freq=0
id=udp_dst_session	ip=192.168.1.10	dos_id=2	exp=3646	pps=0	freq=0
id=udp_scan	ip=192.168.1.110	dos_id=1	exp=649	pps=0	freq=0
id=udp_flood	ip=192.168.1.110	dos_id=2	exp=653	pps=0	freq=0
id=tcp_src_session	ip=192.168.1.110	dos_id=1	exp=5175	pps=0	freq=8
id=tcp_port_scan	ip=192.168.1.110	dos_id=1	exp=175	pps=0	freq=0
id=ip_src_session	ip=192.168.1.110	dos_id=1	exp=5649	pps=0	freq=30
id=udp_src_session	ip=192.168.1.110	dos_id=1	exp=5649	pps=0	freq=22

Which IP addresses are included in the output of this command?

- A. Those whose traffic matches a DoS policy.
- B. Those whose traffic matches an IPS sensor.
- C. Those whose traffic exceeded a threshold of a matching DoS policy.
- D. Those whose traffic was detected as an anomaly by an IPS sensor.

Correct Answer: A

**QUESTION 12**

View the exhibit, which contains the partial output of an IKE real-time debug, and then answer the question below.

```
ike 0: comes 10.0.0.2:500->10.0.0.1:500, ifindex=7....
```

```
ike 0: IKEv1 exchange=Aggressive id=baf47d0988e9237f/2f405ef3952f6fda len=430
```

```
ike 0: in
```

```
BAF47D0988E9237F2F405EF3952F6FDA011004000000000000001AE0400003C000000010000000100
```

```
0000300101000
```

```
ike 0:RemoteSite:4: initiator: aggressive mode get 1st response... ike 0:RemoteSite:4: VID RFC 3947
```

```
4A131c81070358455C5728F20E95452F ike 0:RemoteSite:4: VID DPD AFCAD71368A1F1C96B8696FC77570100
```

```
ike 0:RemoteSite:4: VID FORTIGATE 8299031757A36082C6A621DE000502D7
```

```
ike 0:RemoteSite:4: peer is FortiGate/Fortios (v5 b727)
```





```
ike 0:RemoteSite:4: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3
ike 0:RemoteSite:4: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3C0000000
ike 0:RemoteSite:4: received peer identifier FQDN `remote\`
ike 0:RemoteSite:4: negotiation result
ike 0:RemoteSite:4: proposal id = 1:
ike 0:RemoteSite:4: protocol id = ISAKMP:
ike 0:RemoteSite:4: trans_id = KEY_IKE.
ike 0:RemoteSite:4: encapsulation = IKE/none
ike 0:RemoteSite:4: type=OAKLEY_ENCRYPT_ALG, val=AES_CBC, key ?en=128 ike 0:RemoteSite:4:
type=OAKLEY_HASH_ALG, val=SHA.
ike 0:RemoteSite:4: type-AUTH_METHOD, val=PRESHARED_KEY.
ike 0:RemoteSite:4: type=OAKLEY_GROUP, val=MODP1024.
ike 0:RemoteSite:4: ISAKMP SA lifetime=86400
ike 0:RemoteSite:4: ISAKMP SA baf47d0988e9237f/2f405ef3952f6fda key 16:
B25B6C9384D8BDB24E3DA3DC90CF5E73
ike 0:RemoteSite:4: PSK authentication succeeded
ike 0:RemoteSite:4: authentication OK
ike 0:RemoteSite:4: add INITIAL-CONTACT
ike 0:RemoteSite:4: enc
BAF47D0988E9237F405EF3952F6FDA08100401000000000000080140000181F2E48BFD8E9D603F
ike 0:RemoteSite:4: out
BAF47D0988E9237F405EF3952F6FDA0810040100000000000008C2E3FC9BA061816A396F009A12 ike
0:RemoteSite:4: sent IKE msg (agg_i2send): 10.0.0.1:500-10.0.0.2:500, len=140,
id=baf47d0988e9237f/2 ike 0:RemoteSite:4: established IKE SA baf47d0988e9237f/2f405ef3952f6fda Which
statements about this debug output are correct? (Choose two.)
```

- A. The remote gateway IP address is 10.0.0.1.
- B. It shows a phase 1 negotiation.
- C. The negotiation is using AES128 encryption with CBC hash.
- D. The initiator has provided remote as its IPsec peer ID.

Correct Answer: BD



### QUESTION 13

An administrator has configured two FortiGate devices for an HA cluster. While testing the HA failover, the administrator noticed that some of the switches in the network continue to send traffic to the former primary unit. The administrator decides to enable the setting link-failed-signal to fix the problem. Which statement is correct regarding this command?

- A. Forces the former primary device to shut down all its non-heartbeat interfaces for one second while the failover occurs.
- B. Sends an ARP packet to all connected devices, indicating that the HA virtual MAC address is reachable through a new master after a failover.
- C. Sends a link failed signal to all connected devices.
- D. Disables all the non-heartbeat interfaces in all the HA members for two seconds after a failover.

Correct Answer: A

### QUESTION 14

View the exhibit, which contains the output of a diagnose command, and then answer the question below.

```
# diagnose debug rating
Locale      : english
License     : Contract
Expiration  : Thu Sep 28 17:00:00 20xx
-- Server List (Thu Apr 19 10:41:32 20xx) --
IP          Weight  RTT   Flags  TZ   Packets  Curr Lost  Total Lost
64.26.151.37  10     45    -5     -5   262432   0          846
64.26.151.35  10     46    -5     -5   329072   0          6806
66.117.56.37  10     75    -5     -5   71638    0          275
65.210.95.240 20     71    -8     -8   36875    0          92
209.222.147.36 20     103   DI     -8   34784    0          1070
208.91.112.194 20     107   D      -8   35170    0          1533
96.45.33.65   60     144   0      0    33728    0          120
80.85.69.41   71     226   1      1    33797    0          192
62.209.40.74  150    97    9      9    33754    0          145
121.111.236.179 45     44    F      -5   26410    26226     26227
```

Which statements are true regarding the output in the exhibit? (Choose two.)

- A. FortiGate will probe 121.111.236.179 every fifteen minutes for a response.



- B. Servers with the D flag are considered to be down.
- C. Servers with a negative TZ value are experiencing a service outage.
- D. FortiGate used 209.222.147.3 as the initial server to validate its contract.

Correct Answer: CD

## QUESTION 15

View the exhibit, which contains the output of diagnose sys session list, and then answer the question below.

```
# diagnose sys session list
session info: proto=6 proto_state=01 duration=73 expire=3597 timeout=3600
flags=00000000 sockflag=00000000 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per_ip_shape=
ha_id=0 policy_dir=0 tunnel=/
state-may_dirty synced none app_ntf
statistic (bytes/packets/allow_err): org=822/11/1 reply=9037/15/1 tuples=2
origin->sink: org pre->post, reply pre->post dev=4->2/2->4 gwy=10.200.1.254/10.1.1.10
hook=post dir=org act=snst 10.0.1.10:65464->54.192.15.185:80(10.200.1.1:65464)
pos/ (before, after) 0/(0/0), 0/(0/0)
misc=0 policy_id=1 aut_info=0 chk_client_info=0 vd=0
serial=0000009B tos=ff/ff ips_view=0 app_list=0 app=0
dd_type=0 dd_mode=0
```

If the HA ID for the primary unit is zero (0), which statement is correct regarding the output?

- A. This session is for HA heartbeat traffic.
- B. This session is synced with the slave unit.
- C. The inspection of this session has been offloaded to the slave unit.
- D. This session cannot be synced with the slave unit.

Correct Answer: B

[Latest NSE7\\_EFW Dumps](#)

[NSE7\\_EFW Practice Test](#)

[NSE7\\_EFW Study Guide](#)